

INDUSTRIAL COMPONENT DATA

SAC-4P-100,0-PUR/SH-0,25 1535794 PHOENIX CONTACT

Cable reel

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-100,0-PUR/SH-0,25



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-100,0-PUR/SH-0,25
Catalog number	1535794
Category	Data and communication cable
Minimum order	1 Pcs
Document ID	EO-F97242ACED
Generated	2026-08-01

Product Overview

Cable reel

By meters, Cable ring, shielded, halogen-free PUR, grayish black RAL 7021, 4-conductors, color single conductors: brown, white, blue, black, cable length: 100 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1535794

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 305 (C-2-2017)

GTIN 4046356027366

Weight per Piece (excluding packing) 3,139.100 g

Custom tariff number 85444290

Country of origin DE (Germany)

Dimensions

Length of cable 100 m

General

Number of positions 4

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation LiF9YC11Y

UL AWM style 20549

Conductor cross section 4x 0.25 mm² (Signal line)

AWG signal line 24

Conductor structure signal line 32x 0.10 mm

Core diameter including insulation 1.17 mm ±0.02 mm (Signal line)

Thickness, insulation ≥ 0.21 mm (Core insulation)

approx. 0.5 mm (Outer cable sheath)

Wire colors brown, white, blue, black

Overall twist 4 wires, twisted

Shielding Braided copper wires

Optical shield covering 80 %

External sheath, color black-gray RAL 7021

External cable diameter D 4.7 mm ±0.15 mm

Smallest bending radius, fixed installation 24 mm

Smallest bending radius, movable installation 48 mm

Number of bending cycles 10000000

Bending radius 48 mm

Traversing path 10 m

Traversing rate 3 m/s

Acceleration 10 m/s²

Cable weight 31 kg/km

Outer sheath, material PUR

Material conductor insulation PP

Conductor material Bare Cu litz wires

Insulation resistance ≥ 100 G?·km (at 20 °C)

Conductor resistance max. 78 ?/km (at 20 °C)

Nominal voltage, cable ≤ 300 V

Test voltage, cable ≥ 3000 V

Special properties Flexible cable conduit capable

Silicone-free

Free of substances which would....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-100,0-PUR/SH-0,25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.