

INDUSTRIAL COMPONENT DATA

SAC-8P-100,0-PUR/0,25 1550630 PHOENIX CONTACT Cable reel

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-100,0-PUR/0,25



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-100,0-PUR/0,25
Catalog number	1550630
Category	Data and communication cable
Minimum order	1 Pcs
Document ID	EO-8F9F59BC2F
Generated	2026-08-04

Product Overview

Cable reel

By meters, Cable ring, halogen-free PUR, grayish black RAL 7021, 8-conductors, color single conductors: white, brown, green, yellow, gray, pink, blue, red, cable length: 100 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Key Commercial Data

Orderkey 1550630

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 304 (C-2-2017)

GTIN 4046356170444

Weight per Piece (excluding packing) 4,371.000 g

Custom tariff number 85444995

Country of origin DE (Germany)

Dimensions

Length of cable 100 m

General

Number of positions 8

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation Li9Y11Y

UL AWM style 20549 / 10493 (80°C/300 V)

Conductor cross section 8x 0.25 mm²

AWG signal line 24

Conductor structure signal line 32x 0.10 mm

Core diameter including insulation 1.17 mm ±0.02 mm

Thickness, insulation ≥ 0.21 mm

Wire colors white, brown, green, yellow, gray, pink, blue, red

Overall twist 8 wires around filler to the core

External sheath, color black-gray RAL 7021

Outer sheath thickness approx. 0.8 mm

External cable diameter D 5.9 mm ±0.15 mm

Minimum bending radius, fixed installation 8 x D

Minimum bending radius, flexible installation 10 x D

Number of bending cycles 4000000

Bending radius 59 mm

Traversing path 10 m

Traversing rate 3 m/s

Acceleration 10 m/s²

Cable weight 46 kg/km

Outer sheath, material PUR

Material, filler PE

Material conductor insulation PP

Conductor material Bare Cu litz wires

Conductor resistance ≤ 78 Ω/km

Cable capacity ≤ 70 pF/m

Wave impedance 100 Ω ±15 % (with 1 MHz)

Conductor inductance approx. 0.6 mH/km (with 1 MHz)

Nominal voltage, cable ≤ 300 V

Test voltage, cable ≥ 3000 V

Special properties Flexible cable conduit capable

Silicone-fr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-100,0-PUR/0,25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.