

INDUSTRIAL COMPONENT DATA

FL-PP-RJ45-SCC/SC045 2904577 PHOENIX CONTACT Patch panels

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL-PP-RJ45-SCC/SC045



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL-PP-RJ45-SCC/SC045
Catalog number	2904577
Category	Patch panel copper (twisted pair)
Minimum order	1 Pcs
Document ID	EO-ACF6DB4493
Generated	2026-07-29

Product Overview

Patch panels

Cable Sharing module, two RJ45 female connectors with Ethernet occupancy (top cable output) on 8 spring connection terminals, CAT5e, 10/100 Mbit/s, rail mounting, IP20, selectable symmetrical rail protection contact with jumper

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Safety

Additional Product Information

Key Commercial Data

Orderkey 2904577

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 347 (C-6-2017)

GTIN 4046356864541

Weight per Piece (excluding packing) 114.000 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Width 56 mm

Height 90 mm

Depth 51 mm

Ambient conditions

Ambient temperature (operation) -10 °C ... 50 °C

Degree of protection IP20

General

Mounting position any

Net weight 114 g

Color green

Degree of pollution 2

Overvoltage category II

Serial interface

Interface 1 Ethernet interface, 10/100Base-T(X) in acc. with IEEE 802.3u

No. of ports 1

Connection method Spring-cage connection

Transmission length 100 m (including patch cables)

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 1 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 16

Pin assignment 1,2,3,6

4,5,7,8

Serial transmission speed 10/100 Mbps

Interface 2 Ethernet interface, 10/100Base-T(X) in acc. with IEEE 802.3u

No. of ports 1

Connection method RJ45 CAT5e

Pin assignment 1,2,3,6

1,2,3,6

Standards and Regulations

Designation Air clearances and creepage distances

Standards/regulations DIN EN 50178

Rated insulation voltage 50 V

Rated surge voltage 0.5 kV

Insulation Basic insulation

Degree of pollution 2

Overvoltage category II

Noxious gas test ISA-S71.04-1985 G3 Harsh Group A

Environmental Product Compliance

China RoHS Env...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL-PP-RJ45-SCC/SC045 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.