

INDUSTRIAL COMPONENT DATA

SD-WMTB (70X10) VA 0826585 PHOENIX CONTACT Carrier for conductor marking collar

Brand: PHOENIX CONTACT | Manufacturer Part Number: SD-WMTB (70X10) VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SD-WMTB (70X10) VA
Catalog number	0826585
Category	Cable coding system
Minimum order	50 Pcs
Document ID	EO-B874E50C60
Generated	2026-08-04

Product Overview

Carrier for conductor marking collar

Conductor identification sleeve holder, silver, unlabeled, mounting class: Mounting with cable ties, cable diameter: > 16 mm, usable surface: 70 x 10 mm

Carrier for conductor marking collar, silver, unlabeled, mounting type: Assembly with cable ties, cable diameter: > 16 mm, text field height: 10 mm, text field width: 70 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Marker carrier cable

Type Marking strip/label

Data management status

Article revision 00

DimensionsWidth 10 mm

Text field width 70.00 mm

Text field height 10.00 mm

Length 70 mm

External dimensions

Outside diameter 10 mm ... 305 mm

Material specificationsColor silver

Material Stainless steel

Cable/line External cable diameter > 16.00 mm

Environmental and real-life conditions Scratch test for the determining scratch resistance

Specification DIN EN ISO 1518-1:2019-10 (following)

Requirements ≥ 5 N

Result Test passed

Tesafilm test

Specification DIN EN ISO 2409:2013 (following)

Result Test passed

UV resistance

Specification ISO 4892-2:2013-03 (following)

Result Test passed

Test duration 96 h

Wipe resistance of inscriptions

Specification DIN EN 61010-1 (VDE 0411-1):2011-07

DIN EN 62208 (VDE 0660-511):2012-06 (in parts)

Isopropyl

[CAS No. 67-63-0] Test passed

n-Hexane

[CAS No. 110-54-3] Test passed

Water + Petroleum ether

[CAS No. 64742-82-1] Test passed

Specification ISO 175:2010 (following)

Test duration 168 h

Ambient conditions

Ambient temperature (operation) -80 °C ... 400 °C

Recommended ambient temperature (storage/transport) 23 °C

Recommended humidity (storage/transport) 50 % (Storage in a dry and dark place in the original packaging is recommended)

Shelf life 24 months

Standards and regulations Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Mounting Mounting type Assembly with cable ties

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SD-WMTB (70X10) VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.