

INDUSTRIAL COMPONENT DATA

CASE PTFIX L-BOXX DE 1092040 PHOENIX CONTACT 130 distribution blocks in cross section of 0.14 ... 4 mm², 60..

Brand: PHOENIX CONTACT | Manufacturer Part Number: CASE PTFIX L-BOXX DE



Manufacturer	PHOENIX CONTACT
MPN / Reference	CASE PTFIX L-BOXX DE
Catalog number	1092040
Category	Installation clamp for meters
Minimum order	1 Pcs
Document ID	EO-8F7DF486C7
Generated	2026-08-04

Product Overview

130 distribution blocks in cross section of 0.14 ... 4 mm², 60 DIN rail adapter, 20x screw flanges, plug-in bridges, and marking

PTFIX starter set in a practical Sortimo L-BOXX 102 system case. 130 distribution blocks for 0.14 mm² cable cross-sections ... 10 mm², 60 DIN rail adapters, 20 overhead fasteners (screw), plug-in bridges and lettering

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > FIX block System

Additional Product Information

Key Commercial Data

Orderkey 1092040

Packing unit 1

GTIN 4055626906911

Custom tariff number 85369010

General

Set Items

Standards and Regulations

Classifications

General

Set consists of 3273352 PTFIX 6/12X2,5 GY

3273354 PTFIX 6/12X2,5 BU

3273356 PTFIX 6/12X2,5 RD
1091671 PTFIX 6/12X2,5 GNYE
3273264 PTFIX 6X2,5 GY
3273266 PTFIX 6X2,5 BU
3273268 PTFIX 6X2,5 RD
1091668 PTFIX 6X2,5 GNYE
1028067 PTFIX 2X2,5 GY
1028068 PTFIX 2X2,5 BU
1028069 PTFIX 2X2,5 RD
1091665 PTFIX 2X2,5 GNYE
3274054 PTFIX-NS35
3274056 PTFIX-NS35A
3274060 PTFIX-F
3030161 FBS 2-5
0804183:0001 SK 5/3,8:FORTL.ZAHLEN 1-10
0804183:0011 SK 5/3,8:FORTL.ZAHLEN 11-20
0804206 SK 5/3,8: L1-N,PE
Number of levels 1

Color gray

Flammability rating according to UL 94 V0

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Open side panel No

Back to topStandards and Regulations

Flammability rating according to UL 94 V0

Back to topArticles in set

Distribution block PTFIX 6/12X2,5 GY 3273352

Distribution block, Basic terminal block with supply, The blocks can be bridged with one another via the conductor shaft. For corresponding plug-in bridges, see accessories, nom. voltage: 450 V, nominal current: 24 A, connection method: Push-in connection, Push-in connection, number of connections: 13, cross section: 0.14 mm² - 4 mm², AWG: 26 - 12, width: 41 mm, height: 21.7 mm, color: gray, mounting type: for snapping onto a DIN rail adapter, Adapter plate

DownloadsTechnical data

Distribution b...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CASE PTFIX L-BOXX DE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.