

## INDUSTRIAL COMPONENT DATA

# CC1,5-TS-2,10M AU 1029394 PHOENIX CONTACT Crimp contact, contact diameter: 1.5 mm, turned, Pin, contact ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: CC1,5-TS-2,10M AU



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | PHOENIX CONTACT                   |
| MPN / Reference | CC1,5-TS-2,10M AU                 |
| Catalog number  | 1029394                           |
| Category        | Contact for industrial connectors |
| Minimum order   | 100 Pcs                           |
| Document ID     | EO-E5610E05D7                     |
| Generated       | 2026-08-06                        |

## Product Overview

Crimp contact, contact diameter: 1.5 mm, turned, Pin, contact material: CuZn, contact surface: Ni/Au, connection cross section: 1.5 mm<sup>2</sup> ... 1.5 mm<sup>2</sup> AWG 14 ... 14

Set contact, contact diameter: 1.5 mm, machined, Pin, contact material: CuZn, surface contacts: Ni/Au, connection section: 1.5 mm<sup>2</sup> ... 1.5 mm<sup>2</sup> AWG 14 ... 14

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                     |
|--------------|-----------------------------------------------------|
| Catalog path | PHOENIX CONTACT > QUICKON Installation System (QPD) |
|--------------|-----------------------------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 1029394

Packing unit 1

Catalog page Page 278 (C-2-2019)

GTIN 4055626530888

Custom tariff number 85366990

Drawings

Mechanical characteristics

Material data

Classifications

Ambient conditions

General

Environmental Product Compliance

Drawings

Dimensional drawing

Crimp contact, diameter: 1.5 mm

[Back to top](#)Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C

[Back to top](#)Mechanical characteristics

Conductor cross section 1.5 mm<sup>2</sup> ... 1.5 mm<sup>2</sup> (flexible)

Connection cross section AWG 14 ... 14 (flexible)

Contact diameter 1.5 mm

Insertion/withdrawal cycles >= 100

[Back to top](#)General

Type Individual male contact

Connection method Crimp connection

Contact type turned

[Back to top](#)Material data

Contact material CuZn

Contact surface material Ni/Au

[Back to top](#)Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

[Back to top](#)Classifications

eCl@ss

eCl@ss 5.1 27261200

eCl@ss 6.0 27261200

eCl@ss 7.0 27440204

eCl@ss 8.0 27440204

eCl@ss 9.0 27440204

[Back to top](#)ETIM

ETIM 5.0 EC000796

ETIM 6.0 EC000796

ETIM 7.0 EC000796

[Back to top](#)

ETIM for 1029394 Connectors (EC000796)

Feature Name

Feature Value

Contact type (EF001587)

Pin

Ambient temperature (EF002386)

85 °C

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

1.5 mm<sup>2</sup>

Connectable conductor cross section multi-wired (EF00734...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CC1,5-TS-2,10M AU with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.