

INDUSTRIAL COMPONENT DATA

CC1,5-TS-2,10MPE AU 1029398 PHOENIX CONTACT Crimp contact, contact diameter: 1.5 mm, turned, Pin, contac..

Brand: PHOENIX CONTACT | Manufacturer Part Number: CC1,5-TS-2,10MPE AU



Manufacturer	PHOENIX CONTACT
MPN / Reference	CC1,5-TS-2,10MPE AU
Catalog number	1029398
Category	Contact for industrial connectors
Minimum order	25 Pcs
Document ID	EO-C7F19C3731
Generated	2026-08-05

Product Overview

Crimp contact, contact diameter: 1.5 mm, turned, Pin, contact material: CuZn, contact surface: Ni/Au, connection cross section: 1.5 mm² ... 1.5 mm² AWG 14, for the PE or functional ground connection

Crimp contact, contact diameter: 1.5 mm, machined, Male, contact material: CuZn, contact surface: Ni/Au, connection cross-section: 1.5 mm² ... 1.5 mm², AWG 14, for PE or FE connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > QUICKON Installation System (QPD)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1029398

Packing unit 1

Catalog page Page 278 (C-2-2019)

GTIN 4055626531410

Custom tariff number 85366990

Drawings

Mechanical characteristics

Material data

Classifications

Ambient conditions

General

[Environmental Product Compliance](#)

[Drawings](#)

[Dimensional drawing](#)

[Crimp contact, diameter: 1.5 mm](#)

[Back to top](#)[Ambient conditions](#)

[Ambient temperature \(operation\) -40 °C ... 85 °C](#)

[Back to top](#)[Mechanical characteristics](#)

[Conductor cross section 1.5 mm² ... 1.5 mm² \(flexible\)](#)

[Connection cross section AWG 14 \(flexible\)](#)

[Contact diameter 1.5 mm](#)

[Insertion/withdrawal cycles >= 100](#)

[Back to top](#)[General](#)

[Type Individual male contact](#)

[Connection method Crimp connection](#)

[Contact type turned](#)

[Back to top](#)[Material data](#)

[Contact material CuZn](#)

[Contact surface material Ni/Au](#)

[Back to top](#)[Environmental Product Compliance](#)

[REACH SVHC Lead 7439-92-1](#)

[China RoHS Environmentally Friendly Use Period = 50](#)

[For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"](#)

[Back to top](#)[Classifications](#)

[eCl@ss](#)

[eCl@ss 5.1 27261200](#)

[eCl@ss 6.0 27261200](#)

[eCl@ss 7.0 27440204](#)

[eCl@ss 8.0 27440204](#)

[eCl@ss 9.0 27440204](#)

[Back to top](#)[ETIM](#)

[ETIM 5.0 EC000796](#)

[ETIM 6.0 EC000796](#)

[ETIM 7.0 EC000796](#)

[Back to top](#)

[ETIM for 1029398 Connectors \(EC000796\)](#)

[Feature Name](#)

[Feature Value](#)

[Contact type \(EF001587\)](#)

[Pin](#)

[Ambient temperature \(EF002386\)](#)

[85 °C](#)

[Connectable conductor cross section fine-strand without cable end sleeve \(EF007341\)](#)

[1.5 mm²](#)

[Connectable conductor cross section multi-wired \(EF007343\)](#)

[1.5....](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CC1,5-TS-2,10MPE AU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.