

INDUSTRIAL COMPONENT DATA

CCV 2,5/ 4-GF-LR P20 THR 1837381 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: CCV 2,5/ 4-GF-LR P20 THR



Manufacturer	PHOENIX CONTACT
MPN / Reference	CCV 2,5/ 4-GF-LR P20 THR
Catalog number	1837381
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-A4E1CFDFB3
Generated	2026-08-06

Product Overview

Printed-circuit board connector

Printed circuit board base housing, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: CCV 2.5/.. -GF-LR, pitch: 5 mm, mounting: Weld THR, pin arrangement: Linear pin arrangement, pin length [P]: 2 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, lock: Snap-in lock, fixing type: Lock & Release air clamping (thread), packaging type: boxed packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1837381

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4055626023977

Weight per Piece (excluding packing) 2.770 g

Custom tariff number 85366930

Country of origin DE (Germany)

Dimensions

Length [l] 8.6 mm

Width 30 mm

Pitch 5 mm

Dimension a 15 mm

Width [w] 30 mm

Height [h] 14 mm

Height 12 mm

Length of the solder pin 2 mm

Pin dimensions 1 x 1 mm

Length 8.6 mm

General

Range of articles CCV 2,5/..-GF-LR

Insulating material group IIIa

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 400 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Insulating material LCP

Flammability rating according to UL 94 V0

Color black

Number of positions 4

Packaging information

Type of packaging packed in cardboard

Pieces per package 50

Denomination packing units Pcs.

Standards and Regulations

Connection in acc. with standard EN-VDE

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 13.239121409

ETIM for 1837381 Connectors (EC002637)

Feature Name**Feature Value**

Connector m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CCV 2,5/ 4-GF-LR P20 THR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.