

INDUSTRIAL COMPONENT DATA

CCV 2,5/ 7-GF-5,08 P26 AU THR 1017372 PHOENIX CONTACT Feed-through header CCV 2,5/ 7-GF-5,08 P26 AU THR 1017..

Brand: PHOENIX CONTACT | Manufacturer Part Number: CCV 2,5/ 7-GF-5,08 P26 AU THR



Manufacturer	PHOENIX CONTACT
MPN / Reference	CCV 2,5/ 7-GF-5,08 P26 AU THR
Catalog number	1017372
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-8CD58771C1
Generated	2026-08-05

Product Overview

Feed-through header - CCV 2,5/ 7-GF-5,08 P26 AU THR - 1017372

Printed circuit board base housing, nominal section: 2.5 mm², color: black, nominal current: 12 A, dimensioning voltage (III/2): 320 V, contact surface: Gold, contact type: Male, Number of potentials: 7, Number of rows: 1, Number of poles per row: 7, number of connections: 7, family of articles: CCV 2.5/.. -GF, pitch: 5.08 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, Stecksystem: CLASSIC COMBICON, Locking: Screw lock, packaging type: boxed

PCB headers, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 7, pitch: 5.08 mm, color: black, contact surface: Gold, mounting: THR soldering, pin layout: Linear pinning, solder pin [P]: 2.6 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1017372

Packing unit 1

GTIN 4055626500621

Custom tariff number 85366930

Dimensions

Standards and Regulations

Classifications**General****Environmental Product Compliance****Dimensions**

Length [l] 8.57 mm

Width 45.67 mm

Pitch 5.08 mm

Dimension a 30.48 mm

Width [w] 45.67 mm

Height [h] 14.6 mm

Height 12 mm

Length of the solder pin 2.6 mm

Pin dimensions 1 x 1 mm

Length 8.57 mm

[Back to top](#)General

Range of articles CCV 2,5/..-GF

Connection in acc. with standard EN-VDE

Color black

Number of positions 7

[Back to top](#)Standards and Regulations

Connection in acc. with standard EN-VDE

[Back to top](#)Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50 years

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

[Back to top](#)Classifications

eCI@ss

eCI@ss 8.0 27440402

eCI@ss 9.0 27440402

[Back to top](#)ETIM

ETIM 5.0 EC002637

ETIM 6.0 EC002637

ETIM 7.0 EC002637

[Back to top](#)**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / CCV 2,5/ 7-GF-5,08 P26 AU THR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.