

## INDUSTRIAL COMPONENT DATA

**CCV 2,5/ 7-GF-5,08 P26AUTHRR88 1020352 PHOENIX  
CONTACT Feed-through header CCV 2,5/ 7-GF-5,08  
P26AUTHRR88 10..**

Brand: PHOENIX CONTACT | Manufacturer Part Number: CCV 2,5/ 7-GF-5,08 P26AUTHRR88



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | CCV 2,5/ 7-GF-5,08 P26AUTHRR88  |
| Catalog number  | 1020352                         |
| Category        | Printed circuit board connector |
| Minimum order   | 140 Pcs                         |
| Document ID     | EO-6F5CD40D53                   |
| Generated       | 2026-08-04                      |

**Product Overview**

Feed-through header - CCV 2,5/ 7-GF-5,08 P26AUTHRR88 - 1020352

Printed circuit board base housing, nominal section: 2.5 mm<sup>2</sup>, color: black, nominal current: 12 A, dimensioning voltage (III/2): 320 V, contact surface: Gold, contact type: Male, Number of potentials: 7, Number of rows: 1, Number of poles per row: 7, number of connections: 7, family of articles: CCV 2.5/.. -GF, pitch: 5.08 mm, mounting: Weld THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, Stecksystem: CLASSIC COMBICON, Locking: Screw lock, packing type: 88 mm wide strap

PCB headers, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm<sup>2</sup>, number of positions: 7, pitch: 5.08 mm, color: black, contact surface: Gold, mounting: THR soldering, pin layout: Linear pinning, solder pin [P]: 2.6 mm

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path PHOENIX CONTACT &gt; PCB Connectors (PCC)

**Additional Product Information**

Key Commercial Data

Orderkey 1020352

Packing unit 1

GTIN 4055626510330

Custom tariff number 85366930

[Dimensions](#)

[Standards and Regulations](#)

[Classifications](#)

[General](#)

[Environmental Product Compliance](#)

[Dimensions](#)

Length [ l ] 8.57 mm

Width 45.67 mm

Pitch 5.08 mm

Dimension a 30.48 mm

Width [ w ] 45.67 mm

Height [ h ] 14.6 mm

Height 12 mm

Length of the solder pin 2.6 mm

Pin dimensions 1 x 1 mm

Length 8.57 mm

[Back to top](#)[General](#)

Range of articles CCV 2,5/..-GF

Connection in acc. with standard EN-VDE

Color black

Number of positions 7

[Back to top](#)[Standards and Regulations](#)

Connection in acc. with standard EN-VDE

[Back to top](#)[Environmental Product Compliance](#)

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50 years

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

[Back to top](#)[Classifications](#)

eCl@ss

eCl@ss 4.0 27260700

eCl@ss 4.1 27260700

eCl@ss 5.0 27260700

eCl@ss 5.1 27260700

eCl@ss 6.0 27260700

eCl@ss 7.0 27440402

eCl@ss 8.0 27440402

eCl@ss 9.0 27440402

[Back to top](#)[ETIM](#)

ETIM 5.0 EC002637

ETIM 6.0 EC002637

ETIM 7.0 EC002637

[Back to top](#)

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CCV 2,5/ 7-GF-5,08 P26AUTHRR88 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.