

INDUSTRIAL COMPONENT DATA

CCVA 2,5/ 5-G-5,08P14CR3THRR56 1070733 PHOENIX CONTACT Feed-through header CCVA 2,5/ 5-G-5,08P14CR3THRR56 10..

Brand: PHOENIX CONTACT | Manufacturer Part Number: CCVA 2,5/ 5-G-5,08P14CR3THRR56



Manufacturer	PHOENIX CONTACT
MPN / Reference	CCVA 2,5/ 5-G-5,08P14CR3THRR56
Catalog number	1070733
Category	Printed circuit board connector
Minimum order	140 Pcs
Document ID	EO-8E5B4380D1
Generated	2026-08-05

Product Overview

Feed-through header - CCVA 2,5/ 5-G-5,08P14CR3THRR56 - 1070733

Printed circuit board base housing, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of rows: 1, number of poles: 5, family of articles: CCVA 2.5/.. -G, pitch: 5.08 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 1.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: 56 mm wide strap

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

PCB headers, number of positions: 5, pitch: 5.08 mm, color: black

Key Commercial Data

Orderkey 1070733

Packing unit 1

GTIN 4055626749785

Custom tariff number 85366930

Dimensions

Length [L] 8.6 mm

Width 28.2 mm

Pitch 5.08 mm

Dimension a 20.32 mm

Width [w] 28.2 mm

Height [h] 13.4 mm

Height 12 mm

Length of the solder pin 1.4 mm

Length 8.6 mm

General

Range of articles CCVA 2,5/..-G

Color black

Number of positions 5

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 5.1 27260700

eCl@ss 6.0 27260700

eCl@ss 7.0 27440402

eCl@ss 8.0 27440402

eCl@ss 9.0 27440402

ETIM

ETIM 5.0 EC002637

ETIM 6.0 EC002637

ETIM 7.0 EC002637

ETIM for 1070733 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

5.08 mm

Modular spacing connections (EF006827)

5.08 mm

Rated current I_n (EF008250)

12 A

Rated voltage (EF000228)

320 V

Rated surge voltage (EF002993)

4 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Material of contact surface (EF004020)

Tin

Type of electric connection (EF003961)

Other

Diameter connection pin (EF006823)

1.6 mm

Length pin (EF006825)

1.4 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Black

Inflammability class of insulation material according to UL94 (EF002521)

V0

O...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CCVA 2,5/ 5-G-5,08P14CR3THRR56 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.