

INDUSTRIAL COMPONENT DATA

CK2,5-ED-3,00BU AG 1663695 PHOENIX CONTACT Crimp contact

Brand: PHOENIX CONTACT | Manufacturer Part Number: CK2,5-ED-3,00BU AG



Manufacturer	PHOENIX CONTACT
MPN / Reference	CK2,5-ED-3,00BU AG
Catalog number	1663695
Category	Contact for industrial connectors
Minimum order	100 Pcs
Document ID	EO-FEB1A73007
Generated	2026-08-06

Product Overview

Crimp contact

Crimped contact, contact diameter: 2.5 mm, machined, Female, contact material: Copper alloy, contact surface: Hard silver, connection cross-section: 3 mm² ... 3 mm², 12 AWG

Crimp contact, contact diameter: 2.5 mm, turned, Socket, contact material: Copper alloy, contact surface: silver-plated, connection cross section: 3 mm² ... 3 mm², AWG 12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Technical dataNotesGeneral for HC-M-06..., HC-M-HV-, HC-M-08-, HC-M-20-, HC-A..., HC-B..., HC-BB..., HC-BBB..., and HC-HV contact carriers

MountingAssembly note The quality of a crimp connection is determined by DIN EN 60352-2.

Product propertiesProduct type Crimp contact

Series HC-M-06

HC-M-HV

HC-M-08

HC-A

HC-BB

HC-B

HC-HV

Type Individual female contact
Contact material type turned
Data management status
Article revision 04
Connection dataConnection method Crimp connection
Contact connection type Socket
Connection technology Crimp connection
Conductor cross section 3 mm² ... 3 mm²
Connection cross section AWG 12
Stripping length of the individual wire 7.5 mm (9.5 mm at HC-M-HV...)
Conductor cross section flexible 3 mm² ... 3 mm²
Material specificationsContact material Copper alloy
Contact surface material silver-plated
DimensionsDimensional drawing
Width 4.5 mm
Height 4.5 mm
Depth 22.3 mm
Mechanical characteristics
Contact diameter 2.5 mm
Mechanical propertiesMechanical data
Insertion/withdrawal cycles >= 500
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -40 °C ... 125 °C
ETIM for 1663695 Connectors (EC000796)
Feature Name
Feature Value
Contact type (EF001587)
Bus
Ambient temperature (EF002386)
125 °C
Connectable conductor cross section fine-strand without cable end sleeve (EF007341)
3 mm²
Connectable conductor cross section solid-core (EF007337)
3 mm²
Connectable conductor cross section multi-wired (EF007343)
3 mm²
Type of electric...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CK2,5-ED-3,00BU AG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.