

INDUSTRIAL COMPONENT DATA

ME MAX 35 LC 3-3 KMGY 2200596 PHOENIX CONTACT

Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 35 LC 3-3 KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME MAX 35 LC 3-3 KMGY
Catalog number	2200596
Category	Electronic enclosure
Minimum order	10 Pcs
Document ID	EO-B88BF80615
Generated	2026-08-04

Product Overview

Electronic housing

Rail housing, Full housing with metal pin, tall design, with ventilation slits, width: 35.2 mm, height: 99 mm, depth: 113.65 mm, color: light gray (7035), cross bridge: Rail bus connector (optional), number of poles cross connector: 5

DIN rail housing, Complete housing with metal foot catch, tall design, with vents, width: 35.2 mm, height: 99 mm, depth: 113.65 mm, color: light gray (similar RAL 7035), cross connection: DIN rail connector (optional), number of positions cross connector: 5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.

Recommendation Material of contact pads for bus connector, galvanic gold (hard gold)

Product propertiesProduct type Complete housing

Housing type DIN rail housing

Housing series ME-MAX

Product family ME MAX 35..

Max. number of positions 48 (pitch: 3.5 mm)

36 (pitch: 5 mm)

24 (pitch: 7.25 mm/7.5 mm)

Number of rows 3

3

Type Complete housing with metal foot catch, tall design

Ventilation openings present yes

Data management status

Article revision 02

DimensionsDimensional drawing

Width 35.2 mm

Height 99 mm

Depth 113.65 mm

Depth from top edge of DIN rail 107 mm

PCB design

PCB thickness 1.4 mm ... 1.8 mm

Material specificationsColor (Housing) light gray (RAL 7035)

Flammability rating according to UL 94 V0

CTI according to IEC 60112 600

Housing material Polyamide

Surface characteristics untreated

Environmental and real-life conditionsPower dissipation single housing for 20 °C

Ambient temperature 20 °C

Reduction factor 1

Mounting position vertical

Power dissipation 7.9 W

Power dissipation single housing for 30 °C

Ambient temperature 30 °C

Reduction factor 0.91

Mounting position vertical

Power dissipation 7.2 W

Power dissipation single housing for 40 °C

Ambient temperature 40 °C

Reduction factor 0.81

Mounting position vertical

Power dissipation 6.4 W

Power dissipation single housing for 50 °C

Ambient temperature 50 °C

Reduction factor 0.7

Mounting position vertical

Power dissipation 5.5 W

Po...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 35 LC 3-3 KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.