

INDUSTRIAL COMPONENT DATA

ME MAX 45 LC 2-2 KMGY 2200071 PHOENIX CONTACT

Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 45 LC 2-2 KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME MAX 45 LC 2-2 KMGY
Catalog number	2200071
Category	Electronic enclosure
Minimum order	10 Pcs
Document ID	EO-DA3B0C1D3D
Generated	2026-08-01

Product Overview

Electronic housing

Rail box, Complete housing with metal pin, tall design, with ventilation slits, width: 45.2 mm, height: 99 mm, depth: 113.65 mm, colour: luminous grey (7035), cross-bridge: Bus connector for rail (optional), number of poles cross connector: 5
DIN rail housing, Full housing with metal pin, high design, with ventilation slits, width: 45.2 mm, height: 99 mm, depth: 113.65 mm, color: light gray (Similar RAL 7035), cross bridge: Bus connector for rail (optional), number of poles cross connector: 5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2200071
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
Catalog page Page 688 (C-1-2013)
GTIN 4046356507103
Weight per Piece (excluding packing) 84.100 g
Custom tariff number 85389099
Country of origin DE (Germany)

General

Housing type DIN rail housing

Housing material Polyamide

Color (RAL) light gray

Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Dimensions

Width 45 mm

Height 99 mm

Depth 114.5 mm

Technical data

Number of positions 24

40

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027180401eCl@ss 4.127180401eCl@ss 5.027180506eCl@ss 5.127180500eCl@ss 6.027180800eCl@ss

7.027182702eCl@ss 8.027182702eCl@ss 9.027182702

ETIM 3.0EC001031ETIM 4.0EC001031ETIM 5.0EC001031ETIM 6.0EC001031

UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC

13.231261501

ETIM for 2200071 Cabinets and enclosures (EC001031)

Feature Name

Feature Value

Width (EF000008)

45.2 mm

Height (EF000040)

99 mm

Depth (EF000049)

113.65 mm

Material (EF002169)

Other

Operating temperature (EF002393)

-40 °C

With integrated PCB-mounting connection system (EF003087)

No

Suitable for...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 45 LC 2-2 KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.