

INDUSTRIAL COMPONENT DATA

P-CO 1N4007/L-R 3032460 PHOENIX CONTACT Component connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: P-CO 1N4007/L-R



Manufacturer	PHOENIX CONTACT
MPN / Reference	P-CO 1N4007/L-R
Catalog number	3032460
Category	Component plug terminal block
Minimum order	10 Pcs
Document ID	EO-AE99CEF8DA
Generated	2026-08-03

Product Overview

Component connector

Component connector, with 1N4007 diode, length: 24.2 mm, width: 5.2 mm, height: 33.3 mm, number of poles: 1, color: gray, mounting class: Snap-in mounting

Component connector, with diode1N4007, depth: 33.3 mm, width: 5.2 mm, height: 24.2 mm, number of positions: 1, color: gray, mounting type: Plug-in mounting

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Component plug terminal block

Number of positions 1

Potentials 1

Data management status

Article revision 03

Connection dataMaximum load current 1 A

DimensionsWidth 5.2 mm

Height 24.2 mm

Depth 33.3 mm

Material specificationsColor gray (RAL 7042)

Flammability rating according to UL 94 V0

Insulating material PA

Static insulating material application in cold -60 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3

Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

Environmental and real-life conditions Ambient conditions

Ambient temperature (operation) -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)

Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)

Ambient temperature (assembly) -5 °C ... 70 °C

Ambient temperature (actuation) -5 °C ... 70 °C

Permissible humidity (storage/transport) 30 % ... 70 %

Mounting Mounting type Plug-in mou...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / P-CO 1N4007/L-R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.