

INDUSTRIAL COMPONENT DATA

P-CO 1N4007/R-L 3032457 PHOENIX CONTACT Component connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: P-CO 1N4007/R-L



Manufacturer	PHOENIX CONTACT
MPN / Reference	P-CO 1N4007/R-L
Catalog number	3032457
Category	Component plug terminal block
Minimum order	10 Pcs
Document ID	EO-B8DA1AA274
Generated	2026-08-03

Product Overview

Component connector

Component connector, with 1N4007 diode, length: 24.2 mm, width: 5.2 mm, height: 33.3 mm, number of poles: 1, color: gray, mounting class: Snap-in mounting

Component connector, with diode1N4007, depth: 33.3 mm, width: 5.2 mm, height: 24.2 mm, number of positions: 1, color: gray, mounting type: Plug-in mounting

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Component plug terminal block

Number of positions 1

Potentials 1

Data management status

Article revision 03

Connection dataMaximum load current 1 A (the maximum current is determined by the diode)

DimensionsWidth 5.2 mm

Height 24.2 mm

Depth 33.3 mm

Material specificationsColor gray (RAL 7042)

Flammability rating according to UL 94 V0

Insulating material PA

Static insulating material application in cold -60 °C

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

Environmental and real-life conditions Ambient conditions

Ambient temperature (operation) -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)

Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)

Ambient temperature (assembly) -5 °C ... 70 °C

Ambient temperature (actuation) -5 °C ... 70 °C

Permissible humidity (operation) 20 % ... 90 %

Permissible humidity (storage/transport) 30 % ... 70 %

Mounting Mounting....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / P-CO 1N4007/R-L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.