

INDUSTRIAL COMPONENT DATA

ME 22,5 TBUS 1,5/ 5-ST-3,81 KMGY 2713722 PHOENIX CONTACT DIN rail bus connectors

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 22,5 TBUS 1,5/ 5-ST-3,81 KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 22,5 TBUS 1,5/ 5-ST-3,81 KMGY
Catalog number	2713722
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-2FCA4225BA
Generated	2026-08-02

Product Overview

DIN rail bus connectors

Bus connectors for rail, color: bright gray, rated current: 8 A (parallel contacts), rated voltage (III/2): 125 V, contact surface: Gold, number of poles: 5, pitch: 3.81 mm, mounting: Rail mounting, lock: without, fixing type: without, packaging type: packed in box, Items with gold contacts, bus connectors for connection with electronics boxes, 5 contacts in parallel

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data

Orderkey 2713722

Packing unit 50 pc

Catalog page Page 667 (C-1-2013)

GTIN 4017918914516

Weight per Piece (excluding packing) 4.950 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Width 22.5 mm

Pitch 3.81 mm

Width [w] 22.5 mm

General

Insulating material group I

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 1.5 kV

Rated voltage (III/3) 125 V

Rated voltage (III/2) 100 V

Rated voltage (II/2) 150 V

Nominal current I_N 8 A

Maximum load current 8 A

Insulating material PA

Flammability rating according to UL 94 V0

Color light gray

Number of positions 5

Standards and Regulations

Connection in acc. with standard CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027180401eCl@ss 4.127180401eCl@ss 5.027180506eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss

7.027440309eCl@ss 8.027440309eCl@ss 9.027440309

ETIM 2.0EC001031ETIM 3.0EC001031ETIM 4.0EC002638ETIM 5.0EC002638ETIM 6.0EC002638

UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC

13.239121409

ETIM for 2713722 Connectors (EC002637)

Feature Name

Feature Value

Modular spacing contacts (EF007326)

3.81 mm

Modular spacing connections (EF006827)

3.81 mm

Rated current I_n (EF008250)

8 A

Rated voltage (EF000228)

125 V

Rated surge voltage (EF002993)

2.5 kV

Ov...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 22,5 TBUS 1,5/ 5-ST-3,81 KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.