

INDUSTRIAL COMPONENT DATA

UDK 4-ILA 500 2775061 PHOENIX CONTACT Component terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UDK 4-ILA 500



Manufacturer	PHOENIX CONTACT
MPN / Reference	UDK 4-ILA 500
Catalog number	2775061
Category	Component terminal block
Minimum order	50 Pcs
Document ID	EO-482227A0A9
Generated	2026-08-01

Product Overview

Component terminal block

Terminal block for components, nominal voltage: 500 V, nominal current: 0.5 A, 1st floor, connection type: Screw connection, Sizing cross-section: 4 mm², cross-section: 0.2 mm² - 6 mm², mounting: NS 35/7.5, NS 35/15, NS 32, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 2775061

Packing unit 50 pc

Catalog page Page 495 (C-1-2017)

GTIN 4017918068417

Weight per Piece (excluding packing) 15.460 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Number of levels 1

Number of connections 4

Nominal cross section 4 mm²

Color black
Insulating material PA
Flammability rating according to UL 94 V2
Rated surge voltage 6 kV
LED voltage range 230 V AC/DC ... 500 V AC/DC
Degree of pollution 3
Overvoltage category III
Insulating material group I
Nominal current IN 0.5 A (see load current diagram.)
Maximum load current 0.5 A (with 6 mm² conductor cross section)
Nominal voltage UN 500 V (to neighboring terminal blocks.)
Open side panel Yes
Shock protection test specification IEC 60529:2001-02
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 7.3 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.2 mm² / 0.2 kg
4 mm² / 0.9 kg
6 mm² / 1.4 kg
Tensile test result Test passed
Conductor cross section tensile test 0.2 mm²
Tractive force setpoint 10 N
Conductor cross section tensile test 4 mm²
Tractive force setpoint 60 N
Conductor cro...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UDK 4-ILA 500 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.