

INDUSTRIAL COMPONENT DATA

UKK 5-DIO/O-U 2791016 PHOENIX CONTACT Component terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UKK 5-DIO/O-U



Manufacturer	PHOENIX CONTACT
MPN / Reference	UKK 5-DIO/O-U
Catalog number	2791016
Category	Component terminal block
Minimum order	50 Pcs
Document ID	EO-0D02736E0C
Generated	2026-08-03

Product Overview

Component terminal block

Terminal block for components, with integrated diode, nominal voltage: 500 V, nominal current: 0.5 A, number of connections: 4, connection type: Screw connection, 1st and 2nd floor, Dimensioning cross-section: 4 mm², cross-section: 0.2 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, NS 32, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2791016

Packing unit 50 pc

Catalog page Page 492 (C-1-2017)

GTIN 4017918072384

Weight per Piece (excluding packing) 15.890 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 2

Number of connections 4

Nominal cross section 4 mm²

Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Nominal current IN 32 A (The nominal current of the diode is 1 A)
Maximum load current 32 A (with 4 mm² conductor cross section)
Nominal voltage UN 500 V (Data is based on the dielectric strength of adjacent terminal blocks or of the DINg rail.)
Open side panel Yes
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 2.5 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.2 mm² / 0.2 kg
4 mm² / 0.9 kg
Tensile test result Test passed
Conductor cross section tensile test 0.2 mm²
Tractive force setpoint 10 N
Conductor cross section tensile test 4 mm²
Tractive force setpoint 60 N
Result of tight fit on support Test passed
Tight fit on carrier....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UKK 5-DIO/O-U with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.