


INDUSTRIAL COMPONENT DATA

UTT 2,5-DIO/U-O 3046663 PHOENIX CONTACT Component terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UTTB 2,5-DIO/U-O



Manufacturer	PHOENIX CONTACT
MPN / Reference	UTT 2,5-DIO/U-O
Catalog number	3046663
Category	Component terminal block
Minimum order	50 Pcs
Document ID	EO-F5DA4F5538
Generated	2026-08-02

Product Overview

Component terminal block

Terminal block for components, The max. current is determined by the diode. Mounted: 1N 4007 diode, reverse voltage: 1300 V, constant limit current: 0.5 A., with integrated diode, nominal voltage: 500 V, nominal current: 0.5 A, connection type: Screw connection, 1st and 2nd floor, Sizing cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, color: gray

Terminal component modular, The maximum current is determined by the diode. Integrated: 1N 4007 diode, blocking voltage: 1300V, permanent limit current: 0.5A., with integrated diode, rated current: 0.5A, connection type: Screw connection, 1. and 2. table, Dimensioning section: 2.5 mm², Section: 0.14 mm² - 4 mm², Mounting type: NS 35/7.5, NS 35/15, Colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

Key Commercial Data

Orderkey 3046663

Packing unit 50 pc

Catalog page Page 223 (C-1-2017)

GTIN 4017918997199

Weight per Piece (excluding packing) 16.280 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Note The max. current is determined by the diode. Installed: Diode 1N 4007, reverse voltage: 1300 V, maximum continuous current: 0.5 A.

Number of levels 2

Number of connections 4

Nominal cross section 2.5 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Nominal current IN 24 A

Maximum load current 28 A (with 4 mm² conductor cross section)

Nominal voltage UN 500 V

Open side panel Yes

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C

Static insulating material application in cold -60 °C

Behavior in fire for rail vehicles (DIN 5510-2) Test passed

Flame test method (DIN EN 60695-11-10) V0

Oxygen index (DIN EN ISO 4589-2) >32 %

NF F16-101, NF F10-102 Class I 2

NF F16-101, NF F10-102 Class F 2

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 -

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTTB 2,5-DIO/U-O with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.