

**INDUSTRIAL COMPONENT DATA**

# PATG 2/12 0827078 PHOENIX CONTACT Conductor marker carrier

Brand: PHOENIX CONTACT | Manufacturer Part Number: PATG 2/12



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | PATG 2/12                       |
| Catalog number  | 0827078                         |
| Category        | Mounting for labelling material |
| Minimum order   | 1000 Pcs                        |
| Document ID     | EO-38EEFC0E33                   |
| Generated       | 2026-08-02                      |

## Product Overview

Conductor marker carrier

Support for conductor signaling, transparent, unlabeled, mounting class: slippage, cable diameter range: 2 ... 4 mm, usable surface: 12 x 4 mm

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                               |
|--------------|-------------------------------|
| Catalog path | PHOENIX CONTACT > MS Material |
|--------------|-------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 0827078

Packing unit 1000 pc

Minimum order quantity 1000 pc

Catalog page Page 256 (C-3-2017)

GTIN 4046356417174

Weight per Piece (excluding packing) 0.160 g

Custom tariff number 39269097

Country of origin DE (Germany)

Dimensions

Length (b) 12 mm

Width (a) 5 mm

Cable diameter 2 mm ... 4 mm

Ambient conditions

Ambient temperature (operation) -50 °C ... 80 °C

General

Color transparent

Type Profile

Components Silicone-free

Flammability rating according to UL 94 V0

Material PVC

RoHS compliant Yes

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Marking mounting type slide on

Min. cross section 2 mm<sup>2</sup>

Max. cross section 4 mm<sup>2</sup>

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.024190219eCl@ss 4.124190219eCl@ss 5.027149103eCl@ss 5.127400400eCl@ss 6.027149100eCl@ss  
7.027149153eCl@ss 8.027400401eCl@ss 9.027400401

ETIM 2.0EC000761ETIM 3.0EC000761ETIM 4.0EC000761ETIM 5.0EC002248

UNSPSC 6.0130211811UNSPSC 7.090139121410UNSPSC 1139121410UNSPSC 12.0139121410UNSPSC  
13.239131504

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PATG 2/12 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.