

**INDUSTRIAL COMPONENT DATA**

# UC-WMC 3,1 (30X4) BU CUS 0824720 PHOENIX CONTACT

## Conductor marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: UC-WMC 3,1 (30X4) BU CUS



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | PHOENIX CONTACT          |
| MPN / Reference | UC-WMC 3,1 (30X4) BU CUS |
| Catalog number  | 0824720                  |
| Category        | Cable coding system      |
| Minimum order   | 1 Pcs                    |
| Document ID     | EO-77DEFFDF39            |
| Generated       | 2026-08-01               |

### Product Overview

Conductor marker

Conductor marker, available: by mats, blue, labeled according to customer's instructions, mounting class: hook, cable diameter range: 1.9 ... 3.1 mm, usable surface: 30 x 4 mm, Number of individual indices: 12

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **PHOENIX CONTACT > CABINET add-on**

### Additional Product Information

Key Commercial Data

Orderkey 0824720

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 165 (C-5-2013)

GTIN 4046356360531

Weight per Piece (excluding packing) 8.700 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Length (b) 30 mm

Width (a) 4 mm

Cable diameter 1.9 mm ... 3.1 mm

**Ambient conditions**

Ambient temperature (operation) -40 °C ... 120 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

**General**

Color blue

Type Card form

Components free from silicone and halogen

Flammability rating according to UL 94 V2

Material PA

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 12

Number of individual labels per row 4

Printability UV LED technology

Device 5147999 BLUEMARK CLED

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Marking mounting type clip on

Result Test passed

Oxygen index (DIN EN ISO 4589-2) 28,2%

Class I 3

Class F 2

R22 HL 1 - HL 2

R23 HL 1 - HL 2

R24 HL 1 - HL 2

**Standards and Regulations**

Wipe resistance DIN EN 61010-...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / UC-WMC 3,1 (30X4) BU CUS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.