

INDUSTRIAL COMPONENT DATA

UC-WMC 7,5 (23X8) 0818179 PHOENIX CONTACT Conductor marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: UC-WMC 7,5 (23X8)



Manufacturer	PHOENIX CONTACT
MPN / Reference	UC-WMC 7,5 (23X8)
Catalog number	0818179
Category	Cable coding system
Minimum order	5 Pcs
Document ID	EO-66785FB958
Generated	2026-08-01

Product Overview

Conductor marker

Conductor marker, Mat, white, unlabeled, labelable with: BLUEMARKIDCOLOR, BLUEMARKID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting class: hook, cable diameter range: 5 ... 7.5 mm, usable area: 23 x 8 mm, Number of individual indexes: 6

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0818179

Packing unit 5 pc

Minimum order quantity 5 pc

Catalog page Page 205 (C-3-2017)

GTIN 4046356133548

Weight per Piece (excluding packing) 10.040 g

Custom tariff number 39269097

Country of origin PL (Poland)

Dimensions

Length (b) 23 mm

Width (a) 8 mm

Cable diameter 5 mm ... 7.5 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 120 °C
General
Color white
Type Card form
Components free from silicone and halogen
Flammability rating according to UL 94 V2
Material PA
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 6
Number of individual labels per row 2
Printability UV LED technology
Plotter
Device 5147999 BLUEMARK CLED
5144615 CMS-P1-PLOTTER
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type clip on
Result Test passed
Oxygen index (DIN EN ISO 4589-2) 28,2%
Class I 3
Class F 2
R22 HL 1 - HL 2
R23 HL 1 - HL 2
R24 HL 1 - HL 2
Min. cross section 6 mm²
Max. cross section 16 mm²
AWG min 10
AWG max 6
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Flammabi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UC-WMC 7,5 (23X8) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.