

INDUSTRIAL COMPONENT DATA

K-3E-M17 M9/010-B01/M17 F8 1619328 PHOENIX CONTACT

Connector in molded plastic on both sides

Brand: PHOENIX CONTACT | Manufacturer Part Number: K-3E-M17 M9/010-B01/M17 F8



Manufacturer	PHOENIX CONTACT
MPN / Reference	K-3E-M17 M9/010-B01/M17 F8
Catalog number	1619328
Category	Power cable less 1 kV, for moving application
Minimum order	2 Pcs
Document ID	EO-187996C688
Generated	2026-08-05

Product Overview

Connector in molded plastic on both sides

Plug-in connector coated with plastic on both sides, series: KST, M17-Female, straight coated by plastic extrusion, number of poles: 3+PE, Lock type: Screw lock, to M17-Male, straight coated by plastic extrusion, number of poles: 3+PE, cable length: 10 m, shielded: yes, outer wrap color: orange RAL 2003, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1243449

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1619328

Packing unit 1 pc

Minimum order quantity 2 pc

Note Made to Order (non-returnable)

Catalog page Page 224 (C-2-2017)

GTIN 4046356830683

Weight per Piece (excluding packing) 2,220.000 g

Custom tariff number 85444290

Country of origin DE (Germany)

Conductor length 10 m

Nominal current 26 A
Connector specifications
Type straight plastic-sheathed
Housing material Zinc die-cast
Thread type M17
Locking type Screw locking
Degree of protection IP67, when in locked state
Number of positions 3+PE
Direction of rotation Standard
Type of contact Socket
Insertion/withdrawal cycles 50
Contact resistance < 0.3 m?
Max. current 25 A
Voltage 630 V
Overvoltage category III
Degree of pollution 3
Rated surge voltage 6 kV
Ambient temperature (operation) -40 °C ... 105 °C
Cable specifications
Type of cable PSLC11Y-J
Shielded yes
Cable structure 4x 2.5 mm²
Cable structure (AWG) 14 AWG/4c
External cable diameter 11.6 mm
Outer sheath, material TPU
Material wire insulation TPM
External sheath, color orange RAL 2003
Nominal voltage, cable 1000 V
Test voltage 4 kV
Rated current 26 A
Smallest bending radius, movable installation 116 mm
Ambient temperature for fixed installation -50 °C ... 80 °C
Ambient temperature for flexible installation -20 °C ... 70 °C
Connector specifications (second page)
Type straight plastic-sheathed
Housing material Zinc die-cast
Thread type M17
Degree of protection IP67, when in locked state
Number of positions 3+PE
Direction of rotation Standa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / K-3E-M17 M9/010-B01/M17 F8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.