

**INDUSTRIAL COMPONENT DATA**

# K-7E-M40 M9/010-D03/M40 F8 1620384 PHOENIX CONTACT

## Connector in molded plastic on both sides

Brand: PHOENIX CONTACT | Manufacturer Part Number: K-7E-M40 M9/010-D03/M40 F8



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | PHOENIX CONTACT            |
| MPN / Reference | K-7E-M40 M9/010-D03/M40 F8 |
| Catalog number  | 1620384                    |
| Category        | Flexible cable             |
| Minimum order   | 2 Pcs                      |
| Document ID     | EO-73C45E4239              |
| Generated       | 2026-08-04                 |

### Product Overview

Connector in molded plastic on both sides

Plug-in connector coated with plastic on both sides, series: KSM, M40-Female, straight coated by plastic extrusion, number of poles: 4+3+PE, Lock type: Screw lock, to M40-Male, straight coated by plastic extrusion, number of poles: 4+3+PE, cable length: 10 m, shielded: yes, outer wrap color: orange RAL 2003

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                                 |
|--------------|-------------------------------------------------|
| Catalog path | PHOENIX CONTACT > Field Device Connectors (FDC) |
|--------------|-------------------------------------------------|

### Additional Product Information

Key Commercial Data

Orderkey 1620384

Packing unit 1 pc

Minimum order quantity 2 pc

Note Made to Order (non-returnable)

Catalog page Page 231 (C-2-2017)

GTIN 4046356833790

Weight per Piece (excluding packing) 2,220.000 g

Custom tariff number 85444290

Country of origin DE (Germany)

Conductor length 10 m

Nominal current 26 A

## Connector specifications

Type straight plastic-sheathed

Thread type M40

Locking type Screw locking

Degree of protection IP67, when in locked state

Number of positions 4+3+PE

Direction of rotation Standard

Type of contact Socket

Insertion/withdrawal cycles 50

Contact resistance &lt; 0.3 mΩ

Max. current 70 A

Voltage 630 V

Overvoltage category III

Degree of pollution 3

Rated surge voltage 6 kV

Ambient temperature (operation) -40 °C ... 105 °C

## Cable specifications

Type of cable PSLC11Y-J

Shielded yes

Cable structure 4 x 2.5 mm<sup>2</sup> + 2 x 2 x 1.0 mm<sup>2</sup> StC

External cable diameter 13.5 mm ±0.4 mm

Outer sheath, material PUR

Material wire insulation TPM

External sheath, color orange RAL 2003

Nominal voltage, cable 1000 V

Test voltage 4 kV (2 kV signal)

Smallest bending radius, movable installation 135 mm

Number of bending cycles 10000000

Bending radius 135 mm

Traversing path 6 m

Acceleration 5 m/s<sup>2</sup>

Ambient temperature for fixed installation -40 °C ... 80 °C

Ambient temperature for flexible installation -20 °C ... 60 °C

Special properties Flexible cable conduit capable

Flame resistance IEC 332-1

Halogen-free DIN VDE 0472

Connector specifications (second page)

Type straight p...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / K-7E-M40 M9/010-D03/M40 F8 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.