

INDUSTRIAL COMPONENT DATA

SACC-CI-M12MS-4CON-L180 THR SH 1439939 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-CI-M12MS-4CON-L180 THR SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-CI-M12MS-4CON-L180 THR SH
Catalog number	1439939
Category	Contact insert for circular connectors
Minimum order	60 Pcs
Document ID	EO-DEC31D8C74
Generated	2026-08-02

Product Overview

Flush-type connector

Contact holder, Universal, 4-pole, Male connector, straight, M12, coding: A, Printed circuit board mounting, THR solder connection, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1239695

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1439939

Packing unit 60 pc

Minimum order quantity 60 pc

Note Made to Order (non-returnable)

Catalog page Page 257 (C-2-2013)

GTIN 4046356476713

Weight per Piece (excluding packing) 4.510 g

Custom tariff number 85366990

Country of origin DE (Germany)

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

-55 °C ... 85 °C (without mechanical actuation)

Degree of protection IP67 (correctly plugged in and locked)

General

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Rated current at 40°C 4 A

Rated voltage 250 V

Rated surge voltage 2.5 kV

Number of positions 4

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Signal type/category Universal

Status display No

Overvoltage category II

Degree of pollution 3

Connection method THR solder connection

Insertion/withdrawal cycles > 100

Torque 3 Nm ... 4 Nm (Installation-side)

Mounting type PCB mounting

Type of packaging Tray

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Au

Contact carrier material PPA

Sealing material FKM

Cable

Standards/specifications M12 connector IEC 61076-2-101

Ambien...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-CI-M12MS-4CON-L180 THR SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.