

INDUSTRIAL COMPONENT DATA

SACC-DSI-M 8MS-3CON-L180 SH 1455997 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-M 8MS-3CON-L180 SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-M 8MS-3CON-L180 SH
Catalog number	1455997
Category	Circular connector, mounting (PCB)
Minimum order	20 Pcs
Document ID	EO-2BAE9DA921
Generated	2026-08-02

Product Overview

Flush-type connector

Connect. plug. to be apar. wall poster., Universal, 3-pole, Male connector, straight, M8, Back mount, M8 x 1, Wave soldering

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1455997

Packing unit 20 pc

Minimum order quantity 20 pc

Catalog page Page 229 (C-2-2013)

GTIN 4046356605953

Weight per Piece (excluding packing) 6.040 g

Custom tariff number 85366990

Country of origin DE (Germany)

Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Degree of protection IP67

General

Rated current at 40°C 4 A

Rated voltage 50 V AC
60 V DC
Rated surge voltage 1.5 kV
Number of positions 3
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Standards/regulations M8 connector IEC 61076-2-104
Signal type/category Universal
Status display No
Overvoltage category II
Degree of pollution 3
Connection method Solder pins
Torque 1 Nm ... 1.5 Nm (Installation-side)
Mounting type Rear mounting M8 x 1 With flat nut
Material
Flammability rating according to UL 94 HB
Contact material Cu alloy
Contact surface material Au
Contact carrier material PA 6.6
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Additional material specifications EP (Grout material)
Cable
Standards/specifications M8 connector IEC 61076-2-104
Ambient temperature (operation) -25 °C ... 85 °C
Standards and Regulations
Standard designation M8 connector
Standards/regulations IEC 61076-2-104
Flammability rating according to UL 94 HB
Environmental Product Compliance
REACH SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 25;
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
Classifica...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-M 8MS-3CON-L180 SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.