

INDUSTRIAL COMPONENT DATA

SACC-DSI-M12MS-17CON-M16 SH 1441969 PHOENIX CONTACT Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-M12MS-17CON-M16 SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-M12MS-17CON-M16 SH
Catalog number	1441969
Category	Circular connector, mounting (PCB)
Minimum order	20 Pcs
Document ID	EO-03F702EEEF
Generated	2026-07-28

Product Overview

Panel feed-through

Conect. plug. to be apar. poster wall, 17-pole, Male, straight, M12, coding: A, Rear mounting, M16 x 1.5, Soldering pins, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1239755

Rear device connector, 17-pin, Connector, straight, M12, code-d: A, Rear mounting, M16 x 1.5, Shanks, Alternative according to RoHS II without exception 6c (Pb < 0.1 %) Item no.: 1239755

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1441969

Packing unit 20 pc

Minimum order quantity 20 pc

Note Made to Order (non-returnable)

Catalog page Page 251 (C-2-2013)

GTIN 4046356534185

Weight per Piece (excluding packing) 16.580 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length of the solder pin 6 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

-40 °C ... 85 °C (without mechanical actuation)

Degree of protection IP67

General

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Rated current at 40°C 1.5 A

Rated voltage 30 V

Rated surge voltage 0.8 kV

Number of positions 17

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Overvoltage category II

Degree of pollution 3

Connection method Solder pins

Insertion/withdrawal cycles > 100

Torque 3 Nm ... 4 Nm (Installation-side)

Mounting type Rear mounting M16 x 1.5 With flat nut

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Au

Contact carrier material PA 6.6

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Cable

Standards/specifications M12 connector IE...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-M12MS-17CON-M16 SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.