

INDUSTRIAL COMPONENT DATA

SACC-E-M12MS-4CON-PG9/0,5 FFVA 1431432 PHOENIX CONTACT Bus system flat-type plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-E-M12MS-4CON-PG9/0,5 FFVA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-E-M12MS-4CON-PG9/0,5 FFVA
Catalog number	1431432
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-04FC21ADAC
Generated	2026-08-02

Product Overview

Bus system flat-type plug

Conect. plug. to be apar. front wall, 3-pole, Male connector, straight, M12, coding: A, free cable end, Front mounting, Pg9, Single stranded wires, cable length: 0.5 m, 0.34 mm², TPE braided wire, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1239605

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1431432

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 424 (C-2-2017)

GTIN 4046356457545

Weight per Piece (excluding packing) 18.000 g

Custom tariff number 85444290

Country of origin DE (Germany)

Dimensions

Length of cable 0.5 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

Degree of protection IP67

General

Rated current at 40°C 4 A

Rated voltage 250 V

Rated surge voltage 2.5 kV

Number of positions 3

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Overvoltage category II

Degree of pollution 3

Connection method Individual wires

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Ni/Au

Contact carrier material PA66 GF

Material, knurls Stainless steel

Sealing material FKM

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027143423eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss

7.027440103eCl@ss 8.027440103eCl@ss 9.027440102

ETIM 3.0EC001855ETIM 4.0EC000830ETIM 5.0EC002061ETIM 6.0EC002061

UNSPSC 6.0131251501UNSPSC 7.0901...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-E-M12MS-4CON-PG9/0,5 FFVA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.