

INDUSTRIAL COMPONENT DATA

SACC-E-M12MS-8CON-M12 PSCUP 1436440 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-E-M12MS-8CON-M12 PSCUP



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-E-M12MS-8CON-M12 PSCUP
Catalog number	1436440
Category	Circular connector, mounting (without cable)
Minimum order	20 Pcs
Document ID	EO-AD7FB2F97F
Generated	2026-07-28

Product Overview

Flush-type connector

Built-in mounting plug-in connector for sensors/actuators, female, 8-pole, M12, A-coded, front wall mount / screw-on mount with M12 thread, with solder cups, in plastic design

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1436440

Packing unit 20 pc

Minimum order quantity 20 pc

Note Made to Order (non-returnable)

Catalog page Page 241 (C-2-2013)

GTIN 4046356438391

Weight per Piece (excluding packing) 3.970 g

Custom tariff number 85366990

Country of origin DE (Germany)

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

-40 °C ... 85 °C (without mechanical actuation)

Degree of protection IP67

General

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Rated current at 40°C 2 A

Rated voltage 30 V

Rated surge voltage 0.8 kV

Number of positions 8

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Overvoltage category II

Degree of pollution 3

Connection method Solder cup

Insertion/withdrawal cycles > 100

Torque 3 Nm ... 4 Nm (Installation-side)

Mounting type Front mounting M12 x 1 With flat nut

Material

Flammability rating according to UL 94 HB

Contact material CuZn

Contact surface material Au

Contact carrier material PA 6.6

Material, knurls PA 6.6

Sealing material Viton

Cable

Standards/specifications M12 connector IEC 61076-2-101

Standards and Regulations

Standard designation M12 co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-E-M12MS-8CON-M12 PSCUP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.