

INDUSTRIAL COMPONENT DATA

SACC-V-3CON-PG9/A-1L-SV 120V 1527922 PHOENIX CONTACT ????

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-V-3CON-PG9/A-1L-SV 120V



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-V-3CON-PG9/A-1L-SV 120V
Catalog number	1527922
Category	Valve connector (field assembly)
Minimum order	1 Pcs
Document ID	EO-BE4C1B5C70
Generated	2026-08-04

Product Overview

????

Valve Connector, Universal, 3-Pole, Valve Connector A, Screw Connection, Pg9 Cable Gland, Cable Outer Diameter 6 mm ... 8 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > QUICKON Installation System (QPD)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1527922

Packing unit 1 pc

Catalog page Page 110 (PC-2009)

GTIN 4017918980962

Weight per Piece (excluding packing) 25.240 g

Custom tariff number 85366990

Country of origin HU (Hungary)

Dimensions

External diameter 6 mm ... 8 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (valve plug)

Degree of protection IP65

General

Rated current at 40°C 10 A

Rated voltage 110 V

Number of positions 3

Color handle area transparent

Insulation resistance $\geq 100 \text{ M}\Omega$

Status display 1 LED

Protective circuit/component Varistor

Overvoltage category II

Degree of pollution 3

Connection method Screw connection

Conductor cross section $0.34 \text{ mm}^2 \dots 1.5 \text{ mm}^2$

Conductor cross section AWG 22 ... 16

Insertion/withdrawal cycles 50 (Valve connector)

Material

Flammability rating according to UL 94 HB

Valve plug contact material CuSn

Valve plug contact surface material Ni

Valve plug contact insert material PA6

Material housing valve plug PA6

Sealing material NBR

Standards and Regulations

Flammability rating according to UL 94 HB

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

ClassificationseCl@ss 4.027140815eCl@ss 4.127140815eCl@ss 5.027143423eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss
7.027440104eCl@ss 8.027440104eCl@ss 9.027440105

ETIM 2.0EC001121ETIM 3.0EC002062ETIM 4.0EC002062ETIM 5.0EC002062ETIM 6....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEWSend PHOENIX CONTACT / SACC-V-3CON-PG9/A-1L-SV 120V with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.