


INDUSTRIAL COMPONENT DATA

SACC-V-3CON-PG9/A-1L-SV 24V 1527919 PHOENIX CONTACT

Valve connectors

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-V-3CON-PG9/A-1L-SV 24V



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-V-3CON-PG9/A-1L-SV 24V
Catalog number	1527919
Category	Valve connector (field assembly)
Minimum order	1 Pcs
Document ID	EO-57373E8CC6
Generated	2026-08-04

Product Overview

Valve connectors

Valve Connector, Universal, 3-Pole, Valve Connector A, Screw Connection, Pg9 Cable Gland, Cable Outer Diameter 6 mm ... 8 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > QUICKON Installation System (QPD)**

Additional Product Information

Key Commercial Data

Orderkey 1527919

Packing unit 1 pc

Catalog page Page 110 (PC-2009)

GTIN 4017918980993

Weight per Piece (excluding packing) 24.700 g

Custom tariff number 85366990

Country of origin HU (Hungary)

Dimensions

External diameter 6 mm ... 8 mm

Stripping length of the sheath 34 mm (PE cable)

27 mm (Contact 2)

24 mm (Contact 2)

Stripping length of the individual wire 6 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (valve plug)

Degree of protection IP65

General

Rated current at 40°C 10 A

Rated voltage 24 V

Number of positions 3

Color handle area transparent

Insulation resistance $\geq 100 \text{ M}\Omega$

Status display 1 LED

Protective circuit/component Varistor

Overvoltage category II

Degree of pollution 3

Connection method Screw connection

Conductor cross section $0.34 \text{ mm}^2 \dots 1.5 \text{ mm}^2$

Conductor cross section AWG 22 ... 16

Insertion/withdrawal cycles 50 (Valve connector)

Torque 0.8 Nm ... 1 Nm (Pressure nut)

0.4 Nm (Central screw)

0.5 Nm (Contact screw)

Material

Flammability rating according to UL 94 HB

Valve plug contact material CuSn

Valve plug contact surface material Ni

Valve plug contact insert material PA6

Material housing valve plug PA6

Sealing material NBR

Standards and Regulations

Flammability rating according to UL 94 HB

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-V-3CON-PG9/A-1L-SV 24V with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.