

INDUSTRIAL COMPONENT DATA

SACC-MCI-M12MS-4CON/0,5 1440805 PHOENIX CONTACT

Contact carriers

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-MCI-M12MS-4CON/0,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-MCI-M12MS-4CON/0,5
Catalog number	1440805
Category	Contact insert for circular connectors
Minimum order	1 Pcs
Document ID	EO-BF6A9F0EDD
Generated	2026-08-05

Product Overview

Contact carriers

Contact support, 4-pole, Male connector, straight, M12, coding: A, Front mounting, Square flange, Individual braided wires, cable length: 0.5 m, 0.34 mm², TPE braided wire, Alternative product according to RoHS II without exception 6c (Pb< 0.1%)
item code: 1239711

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1440805

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 40 (C-2-2017)

GTIN 4046356533614

Weight per Piece (excluding packing) 11.700 g

Custom tariff number 85444290

Country of origin DE (Germany)

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

Degree of protection IP67

General

Rated current at 40°C 4 A

Rated voltage 250 V

Rated surge voltage 1.5 kV

Number of positions 4

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Overvoltage category II

Degree of pollution 3

Connection method Crimp contacts

Mounting type Front mounting Square flange 25 mm side length

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Au

Contact carrier material PA 6.6

Cable

Cable type TPE litz wire

AWG signal line 22

Conductor structure signal line 0.34 mm

Outer sheath, material TPE

Standards/specifications M12 connector IEC 61076-2-101

Ambient temperature (operation) -40 °C ... 85 °C (cable, fixed installation)

-25 °C ... 85 °C (cable, flexible installation)

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declara..."

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-MCI-M12MS-4CON/0,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.