

## INDUSTRIAL COMPONENT DATA

## VC-AML 4 1607509 PHOENIX CONTACT Contact insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: VC-AML 4



|                 |                                                   |
|-----------------|---------------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                                   |
| MPN / Reference | VC-AML 4                                          |
| Catalog number  | 1607509                                           |
| Category        | Accessories/spare parts for industrial connectors |
| Minimum order   | 10 Pcs                                            |
| Document ID     | EO-90F3DEAB4E                                     |
| Generated       | 2026-08-01                                        |

## Product Overview

## Contact insert

Contact insert, Article family: VARIOCON, construction: VC2, housing material: PA, color: light gray, number of poles: 4, nominal voltage: 690, assigned current: 63 A, Connection type: Connection for printed circuit boards, Contact connection type: Male. Plug-in connectors should be operated only in an inert (unloaded) state.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path PHOENIX CONTACT &gt; Field Device Connectors (FDC)

## Additional Product Information

## Key Commercial Data

Orderkey 1607509

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 26 (C-2-2013)

GTIN 4017918943585

Weight per Piece (excluding packing) 26.240 g

Custom tariff number 85366990

Country of origin PL (Poland)

## General

Note Connectors may only be connected/disconnected when under no load.

Connection technology Solder connection

Connection method Solder connection

Degree of pollution 3

Number of positions 3+PE

Insertion/withdrawal cycles  $\geq 50$

Size VC2

Ambient conditions

Ambient temperature (operation)  $-40\text{ }^{\circ}\text{C} \dots 100\text{ }^{\circ}\text{C}$

Material data

Housing material PA

Contact material CuZn

Contact surface material hard-silver plated

Contact carrier material PA

Electrical characteristics

Rated voltage (III/3) 690 V

Nominal voltage UN 690 V

Rated surge voltage 6 kV

6 kV

Rated current 63 A

70 A

Standards and Regulations

Connection in acc. with standard CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027140816eCl@ss 4.127140816eCl@ss 5.027143424eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss 7.027440205eCl@ss 8.027440205eCl@ss 9.027440205

ETIM 2.0EC000438ETIM 3.0EC000438ETIM 4.0EC000438ETIM 5.0EC000438ETIM 6.0EC000438

UNSPSC 6.0130211923UNSPSC 7.090139121522UNSPSC 1139121522UNSPSC 12.0139121522UNSPSC 13.239121522

ETIM for 1607509 Connectors (EC003557)

Feature Name

Fea...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VC-AML 4 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.