


INDUSTRIAL COMPONENT DATA

VC-AMS 2 1853528 PHOENIX CONTACT Contact insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: VC-AMS 2



Manufacturer	PHOENIX CONTACT
MPN / Reference	VC-AMS 2
Catalog number	1853528
Category	Accessories/spare parts for industrial connectors
Minimum order	50 Pcs
Document ID	EO-DAEE5E2106
Generated	2026-07-29

Product Overview

Contact insert

Contact insert, Product family: VARIOCON, housing material: Polyamide, color: light gray, number of poles: 2, min. conductor section: 0.25 mm², max. conductor section: 4 mm², nominal voltage: 400, assigned current: 20 A, Connection type: Screw connection, Contact connection type: Male. Plug-in connectors should be operated only in an inert (unloaded) state.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1853528

Packing unit 50 pc

Catalog page Page 25 (C-2-2013)

GTIN 4017918127060

Weight per Piece (excluding packing) 7.690 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Note Connectors may only be connected/disconnected when under no load.

Connection technology Screw connection

Connection method Screw connection

Tightening torque 0.5 Nm ... 0.6 Nm
Degree of pollution 3
Number of positions 2
Insertion/withdrawal cycles ≥ 100
Conductor cross section AWG min. 24
Conductor cross section AWG max. 12
2 conductors with same cross section, solid min. 0.2 mm²
2 conductors with same cross section, solid max. 2.5 mm²
2 conductors with same cross section, stranded min. 0.2 mm²
2 conductors with same cross section, stranded max. 1.5 mm²
Conductor cross section 0.2 mm² ... 4 mm²
Connection cross section AWG 24 ... 12
Stripping length of the individual wire 10 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 100 °C
Material data
Housing material PA 6.6
Contact material CuZn
Contact surface material Tin-plated
Contact carrier material PA
Electrical characteristics
Rated voltage (III/3) 400 V
Rated surge voltage 6 kV
6 kV
Rated current 20 A
Standards and Regulations
Halogen-free yes
Connection in acc. with standard CUL
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Category "Manufacture..."

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VC-AMS 2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.