


INDUSTRIAL COMPONENT DATA

VC-TR3/4M-PEA-S2222-SET 1607167 PHOENIX CONTACT

Contact insert set

Brand: PHOENIX CONTACT | Manufacturer Part Number: VC-TR3/4M-PEA-S2222-SET



Manufacturer	PHOENIX CONTACT
MPN / Reference	VC-TR3/4M-PEA-S2222-SET
Catalog number	1607167
Category	Contact insert for rectangular connectors
Minimum order	5 Pcs
Document ID	EO-ABCC3EF7E3
Generated	2026-08-03

Product Overview

Contact insert set

Set of contact holders for the aerial side, bobbin frame with PE, 4 fixing screws, pre-assembled 2-pole contact holders, 6 encoder pins

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1607167

Packing unit 5 pc

Minimum order quantity 5 pc

Note Made to Order (non-returnable)

Catalog page Page 32 (C-2-2013)

GTIN 4017918940942

Weight per Piece (excluding packing) 53.200 g

Custom tariff number 85366990

Country of origin PL (Poland)

General

Connection technology Screw connection

Connection method Screw connection

Tightening torque 0.5 Nm ... 0.6 Nm

Degree of pollution 3

Number of positions 7+PE

Insertion/withdrawal cycles ≥ 100

Size VC3

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section 0.2 mm² ... 4 mm²

Connection cross section AWG 24 ... 12

Ambient conditions

Ambient temperature (operation) -40 °C ... 100 °C

Material data

Housing material PA

Contact material CuZn

Contact surface material Tin-plated

Contact carrier material PA

Electrical characteristics

Rated voltage (III/3) 400 V

Nominal voltage UN 400 V

Rated surge voltage 6 kV

6 kV

Rated current 20 A

20 A

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027140816eCl@ss 4.127140816eCl@ss 5.027260701eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss
7.027440205eCl@ss 8.027440205eCl@ss 9.027...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VC-TR3/4M-PEA-S2222-SET with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.