

INDUSTRIAL COMPONENT DATA

EWR 1665075 PHOENIX CONTACT Contact insertion and removal tool

Brand: PHOENIX CONTACT | Manufacturer Part Number: EWR



Manufacturer	PHOENIX CONTACT
MPN / Reference	EWR
Catalog number	1665075
Category	Accessories/spare parts for industrial connectors
Minimum order	1 Pcs
Document ID	EO-BE7F696ABB
Generated	2026-07-31

Product Overview

Contact insertion and removal tool

Tool for inserting and unlocking, Article family: VARIOCON, min. conductor cross-section: 0.14 mm², max. conductor cross-section: 0.56 mm², Contact connection type: Female+male

Contact insertion and removal tool, Range of articles: VARIOCON, min. conductor cross section: 0.14 mm², max. conductor cross section: 0.56 mm², Contact connection type: Socket + pin

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Technical dataNotesSafety note

Safety note WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.

• WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.

• WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.

• The products are suitable for applications in plant, controller, and electrical device engineering.

• When operating the connectors in outdoor applications, they must be separately protected against environmental

influences.

- Assembled products may not be manipulated or improperly opened.
- Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).
- When using the product in direct connection with third-party manufacturers, the user is responsible.
- For operating voltages > 50 V AC, conductive connector housings must be grounded
- Ensure that the pr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EWR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.