

INDUSTRIAL COMPONENT DATA

PSR-SPP- 24DC/URM4/4X1/2X2/B 2981680 PHOENIX CONTACT Extension module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSR-SPP-24DC/URM4/4X1/2X2/B



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSR-SPP-24DC/URM4/4X1/2X2/B
Catalog number	2981680
Category	Device for monitoring of safety-related circuits
Minimum order	1 Pcs
Document ID	EO-B7D5FC8382
Generated	2026-08-04

Product Overview

Extension module

Single-channel contact expansion with TBUS interface, 4 NO contacts, 1 NC contact, 1 feedback circuit, no delay, according to cat. 4, PL e according to EN ISO 13849, width: 22.5 mm, plug-in push-in terminal block

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Safety
--------------	--------------------------

Additional Product Information

Key Commercial Data

Orderkey 2981680

Packing unit 1 pc

Catalog page Page 265 (C-6-2017)

GTIN 4046356081542

Weight per Piece (excluding packing) 196.500 g

Custom tariff number 85371098

Country of origin DE (Germany)

Dimensions

Width 22.5 mm

Height 112 mm

Depth 114.5 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 55 °C

Ambient temperature (storage/transport) -40 °C ... 70 °C

Max. permissible relative humidity (operation) 75 % (on average, 85% infrequently, non-condensing)

Max. permissible humidity (storage/transport) 75 % (on average, 85% infrequently, non-condensing)

Maximum altitude max. 2000 m (Above sea level)

Input data

Rated control circuit supply voltage US

Nominal input voltage UN 24 V DC

Input voltage range in reference to UN 0.9 ... 1.1

Typical input current at UN 42 mA

Typical response time 10 ms

Typical release time 10 ms

Recovery time 1 s

Status display Green LED

Protective circuit Surge protection Suppressor diode

Output data

Contact type 4 enabling current paths

1 signaling current path

1 confirmation current path

Contact material AgSnO₂

Maximum switching voltage 250 V AC/DC

Minimum switching voltage 15 V AC/DC

Limiting continuous current 6 A (N/O contact, DC1/AC1)

3 A (N/C contact)

Maximum inrush current 6 A (N/O contact, DC1/AC1)

3 A (N/C contact)

Inrush current, minimum 25 mA

Sq. Total current 72 A₂(I_{TH2}= I₁₂+ I₂₂+ I₃₂+ I₄₂)

Interrupting rating (ohmic load) max. 144 W (24 V DC, ? = 0 ms, N/C contact 61/62: 72 W)

288 W (48 V DC, ? = 0 ms, N/C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSR-SPP-24DC/URM4/4X1/2X2/B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.