

**INDUSTRIAL COMPONENT DATA**

# WP-GR HF CTA M40 BK 3241223 PHOENIX CONTACT

## Corrugated tube screw connection

Brand: PHOENIX CONTACT | Manufacturer Part Number: WP-GR HF CTA M40 BK



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | PHOENIX CONTACT     |
| MPN / Reference | WP-GR HF CTA M40 BK |
| Catalog number  | 3241223             |
| Category        | Cable gland         |
| Minimum order   | 10 Pcs              |
| Document ID     | EO-877416C5A6       |
| Generated       | 2026-08-02          |

### Product Overview

Corrugated tube screw connection

Adapter for corrugated pipe, with M40 internal thread, straight, black, IP66, for connecting corrugated pipes to HEAVYCON-EVO plastic screw connections or to the ADVANCE plastic box.

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial plug-in connectors/interfaces**

### Additional Product Information

Key Commercial Data

Orderkey 3241223

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 585 (C-4-2013)

GTIN 4046356860857

Weight per Piece (excluding packing) 41.380 g

Custom tariff number 39269097

Country of origin DE (Germany)

Ambient conditions

Ambient temperature (operation) -40 °C ... 115 °C

Degree of protection IP66

**General**

Color black

Type With strain relief

Internal thread

Components free from silicone, halogen, and cadmium

Flammability rating according to UL 94 V2

Material PA

Assembly instructions The corrugated pipe adapter is used in the screw connection instead of the union nut. Thanks to the adapter, corrugated pipes can be used.

**Standards and Regulations**

Halogen-free yes

Flammability rating according to UL 94 V2

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

**Classifications**

eCl@ss 4.027141131eCl@ss 4.127141131eCl@ss 5.027141131eCl@ss 5.127140900eCl@ss 6.027140900eCl@ss  
7.027439201eCl@ss 8.027439201eCl@ss 9.027144432

ETIM 3.0EC000897ETIM 4.0EC001469ETIM 5.0EC001469ETIM 6.0EC000441

UNSPSC 6.0130211812UNSPSC 7.090139121410UNSPSC 1139121411UNSPSC 12.0139121411UNSPSC  
13.239121411

ETIM for 3241223 Flexible conduit systems (EC001178)

**Feature Name****Feature Value**

Nominal size in inch (EF005462)

**Other**

Degree of protection (IP) (EF005474)

IP66

Revolving thread (EF001757)

No

Type of connection (EF000064)

**Other**

Thread connecti...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / WP-GR HF CTA M40 BK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.