

INDUSTRIAL COMPONENT DATA

HC-B 10-KMQ-H-O1STM25 1460301 PHOENIX CONTACT HEAVYCON B10 coupling housing, with double locking latch, heig..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 10-KMQ-H-O1STM25



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B 10-KMQ-H-O1STM25
Catalog number	1460301
Category	Housing for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-6CC8FF31E4
Generated	2026-08-04

Product Overview

HEAVYCON B10 coupling housing, with double locking latch, height: 77.5 mm, with 1 x M25 thread, straight cable outlet
HEAVYCON B10 coupling housing, with transverse lock, height 77.5 mm, with 1 x M25 thread, straight cable outlet

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Dimensions

Height 77.5 mm

Width 43 mm

Length 73 mm

Ambient conditions

Degree of protection of housing (IP) IP65

Ambient temperature (operation) -40 °C ... 125 °C

General

Note For contact inserts HC-B10, BB18, DD42, M, K8/24

Type B10

Housing type Coupling housings

Locking type With double locking latch

No. of cable outlets 1
Cable exit straight
Screw connection none
Type of the screw connection 1x M25
Housing material Aluminum die-cast
Housing surface material Powder-coated, gray
Seal material NBR
Material lock High-grade steel, handle: PA-GF
Material grip body interlock PA-GF

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 10-KMQ-H-O1STM25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.