

INDUSTRIAL COMPONENT DATA

HC-B 16-KML-H-O1STM40 1460309 PHOENIX CONTACT HEAVYCON B16 coupling housing, with single locking latch, heig..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 16-KML-H-O1STM40



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B 16-KML-H-O1STM40
Catalog number	1460309
Category	Housing for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-9644BE7B35
Generated	2026-08-04

Product Overview

HEAVYCON B16 coupling housing, with single locking latch, height: 82 mm, with 1 x M40 thread, straight cable outlet
HEAVYCON B16 coupling housing, with longitudinal lock, height 82 mm, with 1x M40, straight cable outlet

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Dimensions

Height 82 mm

Width 43 mm

Length 73 mm

Ambient conditions

Degree of protection of housing (IP) IP65

Ambient temperature (operation) -40 °C ... 125 °C

General

Note For contact inserts HC-B16, BB32, BBB40, D40, DD72, HS6, M, K

Type B16

Housing type Coupling housings

Locking type With single locking latch

No. of cable outlets 1
Cable exit straight
Screw connection none
Type of the screw connection 1x M40
Housing material Aluminum die-cast
Housing surface material Powder-coated, gray
Seal material NBR
Material lock Stainless steel, handle: PA
Material grip body interlock PA

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 16-KML-H-O1STM40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.