

INDUSTRIAL COMPONENT DATA

HC-B 24-KML-H-O1STM40 1460326 PHOENIX CONTACT HEAVYCON B24 coupling housing, with single locking latch, heig..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 24-KML-H-O1STM40



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B 24-KML-H-O1STM40
Catalog number	1460326
Category	Housing for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-548E710EBF
Generated	2026-08-01

Product Overview

HEAVYCON B24 coupling housing, with single locking latch, height: 80.5 mm, with 1 x M40 thread, straight cable outlet

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces
--------------	--

Additional Product Information

Dimensions

Height 82 mm

Width 43 mm

Length 120 mm

Ambient conditions

Degree of protection of housing (IP) IP65

Ambient temperature (operation) -40 °C ... 125 °C

General

Note For contact inserts HC-B24, BB46, BBB64, D64, DD108, M

Type B24

Housing type Coupling housings

Locking type With single locking latch

No. of cable outlets 1

Cable exit straight
Screw connection none
Type of the screw connection 1x M40
Housing material Aluminum die-cast
Housing surface material Powder-coated, gray
Seal material NBR
Material lock Stainless steel, handle: PA
Material grip body interlock PA

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 24-KML-H-O1STM40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.