

## INDUSTRIAL COMPONENT DATA

## SC 4/ 5 3042489 PHOENIX CONTACT COMBI receptacle

Brand: PHOENIX CONTACT | Manufacturer Part Number: SC 4/ 5



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | PHOENIX CONTACT          |
| MPN / Reference | SC 4/ 5                  |
| Catalog number  | 3042489                  |
| Category        | Terminal block connector |
| Minimum order   | 50 Pcs                   |
| Document ID     | EO-EF02553AB1            |
| Generated       | 2026-08-01               |

## Product Overview

COMBI receptacle

COMBI coupling, rated voltage: 800 V, rated current: 32 A, number of connections: 2, number of poles: 5, connection type: Spring connection, Sizing cross-section: 4 mm<sup>2</sup>, cross-section: 0.08 mm<sup>2</sup> - 6 mm<sup>2</sup>, color: gray

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path PHOENIX CONTACT &gt; Modular TBs

## Additional Product Information

Key Commercial Data

Orderkey 3042489

Packing unit 50 pc

Note Made to Order (non-returnable)

Catalog page Page 329 (C-1-2017)

GTIN 4046356012621

Weight per Piece (excluding packing) 26.790 g

Custom tariff number 85366990

Country of origin PL (Poland)

General

Number of positions 5

Number of levels 1

Number of connections 2

Nominal cross section 4 mm<sup>2</sup>

Color gray  
Insulating material PA  
Flammability rating according to UL 94 V0  
Area of application Railway industry  
Machine building  
Plant engineering  
Maximum load current 32 A (with 6 mm<sup>2</sup> conductor cross section)  
Rated surge voltage 8 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
Maximum power dissipation for nominal condition 1.02 W  
Maximum load current 32 A (with 6 mm<sup>2</sup> conductor cross section)  
Nominal current I<sub>N</sub> 32 A  
Nominal voltage U<sub>N</sub> 800 V  
Open side panel Yes  
Relative insulation material temperature index (Elec., UL 746 B) 130 °C  
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C  
Static insulating material application in cold -60 °C  
Behavior in fire for rail vehicles (DIN 5510-2) Test passed  
Flame test method (DIN EN 60695-11-10) V0  
Oxygen index (DIN EN ISO 4589-2) >32 %  
NF F16-101, NF F10-102 Class I 2  
NF F16-101, NF F10-102 Class F 2  
Surface flammability NFPA 130 (ASTM E 162) passed  
Specific optical density of smoke NFPA 130 (ASTM E 662) passed  
Smoke gas toxicity NFPA 130 (SMP 800C) passed  
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg  
Fire protection for r...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SC 4/ 5 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.