

INDUSTRIAL COMPONENT DATA

PSR-PS20-1NO-1NC-24DC-SC 2700356 PHOENIX CONTACT

Coupling relay

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSR-PS20-1NO-1NC-24DC-SC



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSR-PS20-1NO-1NC-24DC-SC
Catalog number	2700356
Category	Device for monitoring of safety-related circuits
Minimum order	1 Pcs
Document ID	EO-AC4FDFCB96
Generated	2026-08-05

Product Overview

Coupling relay

SIL 3 High and Low Demand Coupling Relay for High and Low Demand Applications, Couples Digital Output Signals to the Periphery, 1 Trip Circuit, 1 Acknowledgment Circuit, 1 Digital Warning Output, Safe-State-Off Applications, Test Pulse Filter, Fixed Screw Terminal

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Safety
--------------	--------------------------

Additional Product Information

Key Commercial Data

Orderkey 2700356

Packing unit 1 pc

Catalog page Page 281 (C-6-2017)

GTIN 4046356912891

Weight per Piece (excluding packing) 83.500 g

Custom tariff number 85364900

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 6.8 mm

Height 93.1 mm

Depth 102.5 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 70 °C (observe derating)

Ambient temperature (storage/transport) -40 °C ... 85 °C

Max. permissible relative humidity (operation) 75 % (on average, 85% infrequently, non-condensing)

Max. permissible humidity (storage/transport) 75 % (on average, 85% infrequently, non-condensing)

Maximum altitude ≤ 2000 m (Above sea level)

Power supply

Rated control circuit supply voltage US 24 V DC -15 % / +10 % (A1/A2)

20.4 V DC ... 26.4 V DC

Rated control supply current IS typ. 45 mA

Power consumption at US typ. 1.08 W

Inrush current typ. 400 mA (?t s)

Filter time max. 2 ms (at A1-A2; test pulse width)

≥ 100 ms (at A1-A2; test pulse rate)

Diagnostic supply voltage UD 24 V DC -15 % / +10 % (21/A2)

Input current at UD 6 mA (at 21-A2 for UD; depending on load + 100 mA at M1 and 22)

Inrush current at UD typ. 2.5 A (?t D)

Protective circuit Serial protection against polarity reversal Suppressor diode 33 V (A1/A2), 38 V (21/A2)

Relay outputs: enabling current path

Output name Enabling current path

Output description 2 N/O contacts in series, without delay, floating

Number...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSR-PS20-1NO-1NC-24DC-SC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.