

INDUSTRIAL COMPONENT DATA

BC 53,6 DKL R KMGY 2896432 PHOENIX CONTACT Housing cover

Brand: PHOENIX CONTACT | Manufacturer Part Number: BC 53,6 DKL R KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	BC 53,6 DKL R KMGY
Catalog number	2896432
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-7D6B444418
Generated	2026-08-02

Product Overview

Housing cover

Rail box for use in installation distributors according to DIN 43880, Fitted cover (fixed), width: 53.6 mm, height: 45 mm, depth: 8 mm, colour: light grey (7035)

DIN rail enclosure for use in cost allocators in accordance with DIN 43880, snap-on cover (fixed), width: 53.6 mm, height: 45 mm, depth: 8 mm, colour: light grey (similar to RAL 7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2896432

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 699 (C-1-2013)

GTIN 4046356103183

Weight per Piece (excluding packing) 6.800 g

Custom tariff number 85389099

Country of origin DE (Germany)

Item properties

Brief article description Housing cover

Type BC 53,6 DKL R KMGY

Order No. 2896432

Housing type Installation component housing

Type Cover

Dimensions

Width [w] 53.6 mm

Height [h] 45 mm

Depth [d] 8 mm

Material data

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material Polycarbonate

Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Packaging information

Pieces per package 10

Denomination packing units Pcs.

Standards and regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027180401eCl@ss 4.127180401eCl@ss 5.027180506eCl@ss 5.127180500eCl@ss 6.027180800eCl@ss
7.027182702eCl@ss 8.027182702eCl@ss 9.027182702

ETIM 2.0EC001031ETIM 3.0EC001031ETIM 4.0EC000886ETIM 5.0EC001031ETIM 6.0EC001031

UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC
13.231261501

ETIM for 2896432 Low-voltage industrial controls and switchgear (EC002779)

Feature...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BC 53,6 DKL R KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.