

INDUSTRIAL COMPONENT DATA

APT-ME 3034358 PHOENIX CONTACT Cover profile carrier

Brand: PHOENIX CONTACT | Manufacturer Part Number: APT-ME



Manufacturer	PHOENIX CONTACT
MPN / Reference	APT-ME
Catalog number	3034358
Category	Installation clamp for meters
Minimum order	10 Pcs
Document ID	EO-9447D85FC8
Generated	2026-07-31

Product Overview

Cover profile carrier

Cover profile holder, for mounting on symmetrical NS 35/7.5 rail, for clamping the AP-ME cover profile

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data

Orderkey 3034358

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 601 (C-1-2017)

GTIN 4046356324700

Weight per Piece (excluding packing) 19.600 g

Custom tariff number 39269097

Country of origin PL (Poland)

Dimensions

Length (b) 138 mm

Width (a) 2.2 mm

Height (c) 69 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 115 °C

General

Color gray

Flammability rating according to UL 94 V2

Material PA

Result Test passed

Flame test method (DIN EN 60695-11-10) V0

Oxygen index (DIN EN ISO 4589-2) >32 %

Class I 2

Class F 2

Surface flammability (ASTM E 162) passed

Specific optical density of smoke (ASTM E 662) passed

Smoke gas toxicity (SMP 800C) passed

Heat dissipation calorimetric (ASTM E 1354) 28 MJ/kg

R22 HL 1 - HL 3

R23 HL 1 - HL 3

R24 HL 1 - HL 3

R26 HL 1 - HL 3

Standards and Regulations

Flammability rating according to UL 94 V2

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 10.0.127141190eCl@ss 4.027110804eCl@ss 4.127110804eCl@ss 5.027141143eCl@ss 5.127141100eCl@ss
6.027141100eCl@ss 7.027141190eCl@ss 8.027141190eCl@ss 9.027141190
ETIM 3.0EC000012E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / APT-ME with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.