

INDUSTRIAL COMPONENT DATA

E/NS 35 N-APH 3240269 PHOENIX CONTACT Cover profile carrier

Brand: PHOENIX CONTACT | Manufacturer Part Number: E/NS 35 N-APH



Manufacturer	PHOENIX CONTACT
MPN / Reference	E/NS 35 N-APH
Catalog number	3240269
Category	Installation clamp for meters
Minimum order	10 Pcs
Document ID	EO-C8ACA86961
Generated	2026-08-04

Product Overview

Cover profile carrier

Support for cover profile, material:PA, color:gray, Spacer bolt = 0.5 Nm ... 0.6 Nm, for hoods

Backing Plate, Spacer Bolt = 0.5 Nm ... 0.6 Nm, for cover caps, material: PA, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Enclosures connectivity**

Additional Product Information

Key Commercial Data

Orderkey 3240269

Packing unit 10 pc

Minimum order quantity 10 pc

GTIN 4055626049588

Weight per Piece (excluding packing) 30.000 g

Custom tariff number 73269098

Country of origin FR (France)

General

Note Spacer bolt = 0.5 Nm ... 0.6 Nm

Sealing screw M3 x 10 = 0.3 Nm ... 0.4 Nm

Color gray

Material PA

Flammability rating according to UL 94 V0

Dimensions

Width 9.5 mm

Length 48.6 mm

Height 77.5 mm

Height NS 35/7,5 69.50 mm

General

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C

Static insulating material application in cold -60 °C

Behavior in fire for rail vehicles (DIN 5510-2) Test passed

Flame test method (DIN EN 60695-11-10) V0

Oxygen index (DIN EN ISO 4589-2) >32 %

NF F16-101, NF F10-102 Class I 2

NF F16-101, NF F10-102 Class F 2

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3

Standards and Regulations

Flammability rating according to UL 94 V0

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / E/NS 35 N-APH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.