


INDUSTRIAL COMPONENT DATA

VC-AMC 5 1583878 PHOENIX CONTACT Contact carriers

Brand: PHOENIX CONTACT | Manufacturer Part Number: VC-AMC 5



Manufacturer	PHOENIX CONTACT
MPN / Reference	VC-AMC 5
Catalog number	1583878
Category	Housing for rectangular connectors
Minimum order	5 Pcs
Document ID	EO-48C35357CE
Generated	2026-08-01

Product Overview

Contact carriers

Contact support, Family of items: VARIOCON, construction: VC3, housing material: PA 6.6, color: light gray, number of poles: 5, nominal voltage: 690, assigned current: 70 A, Connection type: Crimp connection, Contact connection type: Male. Plug-in connectors should be operated only in an inert (unloaded) state.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1583878

Packing unit 5 pc

Minimum order quantity 5 pc

Note Made to Order (non-returnable)

Catalog page Page 28 (C-2-2013)

GTIN 4046356569637

Weight per Piece (excluding packing) 27.840 g

Custom tariff number 85472000

Country of origin PL (Poland)

General

Note Connectors may only be connected/disconnected when under no load.

Connection technology Crimp connection

Connection method Crimp connection

Degree of pollution 3

Number of positions 4+PE

Insertion/withdrawal cycles ≥ 50

Size VC3

Conductor cross section AWG min. 12

Conductor cross section AWG max. 6

Conductor cross section 4 mm² ... 16 mm²

Ambient conditions

Ambient temperature (operation) -40 °C ... 100 °C

Material data

Housing material PA 6.6

Contact material CuZn

Contact surface material hard-silver plated

Contact carrier material PA

Electrical characteristics

Rated voltage (III/3) 690 V

Rated surge voltage 6 kV

Rated current 70 A

70 A

Standards and Regulations

Halogen-free yes

Connection in acc. with standard CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027140816eCl@ss 4.127140816eCl@ss 5.027143424eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss
7.027440202eCl@ss 8.027440202eCl@ss 9.027440202

ETIM 4.0EC000437ETIM 5.0EC000437ETIM 6.0EC000437

UNSPSC 6.0130211923UNSPSC 7.090139121522UNSPSC 1139121522UNSPSC 12.0139121522UNSPSC 1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VC-AMC 5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.