

INDUSTRIAL COMPONENT DATA

CSD-SL 200S YE 1096101 PHOENIX CONTACT Signal light, 24 V DC, yellow, communication interface, safe diagnost..

Brand: PHOENIX CONTACT | Manufacturer Part Number: CSD-SL 200S YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	CSD-SL 200S YE
Catalog number	1096101
Category	Accessories/spare parts for optic and acoustic signalling equipment
Minimum order	1 Pcs
Document ID	EO-7D6DFB9E36
Generated	2026-08-02

Product Overview

Signal light, 24 V DC, yellow, communication interface, safe diagnostics in accordance with safety standards

Signal light, 24 VDC, IALA yellow Optimum, diameter: 174 mm, protection index: IP65/IP67, Communication interface, Safe diagnostics

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Safety
--------------	--------------------------

Additional Product Information

Key Commercial Data

Orderkey 1096101

Packing unit 1

GTIN 4055626927008

Custom tariff number 85308000

Dimensions

General

Light properties

Environmental Product Compliance

Ambient conditions

Power supply for module electronics

Standards and Regulations

Classifications

Dimensions

Width 174 mm

Height 189 mm

Depth 66 mm

Length 174 mm

[Back to top](#)Ambient conditions

Ambient temperature (operation) -25 °C ... 55 °C

Ambient temperature (storage/transport) -25 °C ... 85 °C

Air pressure (operation) 70 hPa ... 106 kPa (up to 3000 m above sea level)

Air pressure (storage/transport) 70 hPa ... 106 kPa (up to 3000 m above sea level)

Degree of protection IP65/IP67, when installed

[Back to top](#)General

Net weight 1680 g

Diagnostics messages LEDs; temperature, current, voltage, etc. Yes

Mains failure, communication failure Yes

Safe diagnostics (up to SIL 2/PL d) in conjunction with safe modules (safety technology) Yes

Mounting position vertical

Design Operating hours counter

Inrush current max. 12 A (μ-sec-pulse)

[Back to top](#)Power supply for module electronics

Connection method M12 connector

Number of positions 8

Supply voltage 24 V DC (DC)

Supply voltage range 19.2 V DC ... 30 V DC (DC)

Current consumption max. 540 mA (yellow LEDs)

Power consumption typ. 11 W (yellow LEDs)

[Back to top](#)Light properties

Source of light type LED

Number of LEDs 8 (according to IALA recommendation E200-1 and CIE 1931)

Service life, lighting appliance 50000 h

Light color IALA yellow, optimum

Color class C2 (EN 12966)

Lu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CSD-SL 200S YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.