

INDUSTRIAL COMPONENT DATA

CSD-SL 300 GN 30X30 1051088 PHOENIX CONTACT Signal lamp

Brand: PHOENIX CONTACT | Manufacturer Part Number: CSD-SL 300 GN 30X30



Manufacturer	PHOENIX CONTACT
MPN / Reference	CSD-SL 300 GN 30X30
Catalog number	1051088
Category	Monitored LED indicator luminaire
Minimum order	1 Pcs
Document ID	EO-0BD7B4312B
Generated	2026-08-02

Product Overview

Signal lamp

Signal light, 24 VDC, IALA green Optimum, emission angle: 30 °, diameter: 272 mm, protection index: IP65/IP67, Communication interface

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Safety**

Additional Product Information

Key Commercial Data

Orderkey 1051088

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4055626670638

Weight per Piece (excluding packing) 3,860.000 g

Custom tariff number 85308000

Country of origin DE (Germany)

Dimensions

Width 272 mm

Height 291 mm

Depth 68 mm

Length 272 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 55 °C

Ambient temperature (storage/transport) -25 °C ... 85 °C

Air pressure (operation) 70 hPa ... 106 kPa (up to 3000 m above sea level)

Air pressure (storage/transport) 70 hPa ... 106 kPa (up to 3000 m above sea level)

Degree of protection IP65/IP67, when installed

General

Assembly instructions Use of stainless steel fittings (corrosion-resistant)

Net weight 3860 g

Diagnostics messages LEDs; temperature, current, voltage, etc. Yes

Mains failure, communication failure Failsafe

Design Operating hours counter

Inrush current max. 36 A ()

Power supply for module electronics

Connection method M17 hybrid connectors with SPEEDCON locking system

Number of positions 8

Supply voltage 24 V DC (DC)

Current consumption max. 2.73 A (green LEDs)

Power consumption max. 75 W (green LEDs)

Light properties

Source of light type LED

Number of LEDs 30 (according to IALA recommendation E200-1 and CIE 1931)

Service life, lighting appliance 50000 h

Light color IALA green, optimum

Color temperature / wavelength 490...510 nm

Color class C3 (EN 12966)

Luminance L3 (EN 12966)

Luminance ratio R3 (EN 12966)

Phantom light class 5 (EN 12368)

Luminous intensity 6800 C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CSD-SL 300 GN 30X30 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.